

Modular Cooking Range Line thermaline 90 - 500 mm Passthrough open base, GN conform, 2 Sides (H2) -H=450

ITEM #		
MODEL #		
MODEL #		
NAME #		
SIS #		
AIA #		



589193 (MC2BCCEOOO)

Passthrough Open Base, two-side operated, GN - H2

Short Form Specification

Item No.

500 mm wide open passthrough base compartment to store pots, pans, sheet pans, etc. with hygienic design and round edges. Internal frame for heavy duty sturdiness in stainless steel. Flat surface construction, easily cleanable. Open storage space in the base accepts GN 1/1 containers.

IPX5 water resistant certification.

Configuration: Two-side operated freestanding base, hygienic class H2.

Main Features


- All major components may be easily accessed from the front.
- Unit to be placed below modular top appliances to store pots, pans, sheet pans, etc.

Construction


- IPX5 water resistance certification.
- Hygienic design of the open base compartment with large round edges.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Storage space in the base of the appliance that can accept GN1/1 containers.
- Internal frame for heavy duty sturdiness in stainless steel.

APPROVAL:









Key Information:

External dimensions, Width: 589193 (MC2BCCEOOO) 500 mm 900 mm External dimensions, Depth: 450 mm External dimensions, Height: **Cupboard Cavity Dimensions** 340 mm (width): **Cupboard Cavity Dimensions** 330 mm (height): **Cupboard Cavity Dimensions** (depth): 860 mm Net weight: 19 kg





Optional Accessories

 Stainless steel side panel, 900x700mm, freestanding 	PNC 912512	
• Stainless steel front kicking strip, 500mm width	PNC 912631	
 Stainless steel side kicking strip left and right, freestanding, 900mm width 	PNC 912657	
 Stainless steel plinth, freestanding, 500mm width 	PNC 912955	
 Perforated shelf for warming cabinets and cupboard bases (two-side operated for TL90) 	PNC 913236	
 Side reinforced panel only in combination with side shelf, for freestanding units 	PNC 913260	
 Shelf fixation for TL90 two-side operated 	PNC 913280	
Stainless steel dividing panel, 900x700mm, (it should only be used between Electrolux Professional thermaline Modular 90 and thermaline C90)	PNC 913672	
• Stainless steel side panel, 900x700mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions)	PNC 913688	

