



Modular Cooking Range Line
thermaline 90 - 500 mm Passthrough
open base, GN conform, 2 Sides (H2) -
H=450

ITEM # _____
MODEL # _____
NAME # _____
SIS # _____
AIA # _____



589193 (MC2BCCEOOO)

Passthrough Open Base,
two-side operated, GN - H2

Short Form Specification

Item No. _____

500 mm wide open passthrough base compartment to store pots, pans, sheet pans, etc. with hygienic design and round edges. Internal frame for heavy duty sturdiness in stainless steel. Flat surface construction, easily cleanable. Open storage space in the base accepts GN 1/1 containers. IPX5 water resistant certification. Configuration: Two-side operated freestanding base, hygienic class H2.

Main Features

- All major components may be easily accessed from the front.
- Unit to be placed below modular top appliances to store pots, pans, sheet pans, etc.

Construction

- IPX5 water resistance certification.
- Hygienic design of the open base compartment with large round edges.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Storage space in the base of the appliance that can accept GN1/1 containers.
- Internal frame for heavy duty sturdiness in stainless steel.

APPROVAL: _____




Experience the Excellence
www.electroluxprofessional.com




Electrolux
PROFESSIONAL

Modular Cooking Range Line
thermaline 90 - 500 mm Passthrough open
base, GN conform, 2 Sides (H2) - H=450


Front



Side



Top



Key Information:

External dimensions, Width:	
589193 (MC2BCCE000)	500 mm
External dimensions, Depth:	900 mm
External dimensions, Height:	450 mm
Cupboard Cavity Dimensions (width):	340 mm
Cupboard Cavity Dimensions (height):	330 mm
Cupboard Cavity Dimensions (depth):	860 mm
Net weight:	19 kg



Modular Cooking Range Line
thermaline 90 - 500 mm Passthrough open base, GN conform, 2 Sides
(H2) - H=450
The company reserves the right to make modifications to the products
without prior notice. All information correct at time of printing.

2025.09.05

Optional Accessories

- Stainless steel side panel, 900x700mm, freestanding PNC 912512 ☐
- Stainless steel front kicking strip, 500mm width PNC 912631 ☐
- Stainless steel side kicking strip left and right, freestanding, 900mm width PNC 912657 ☐
- Stainless steel plinth, freestanding, 500mm width PNC 912955 ☐
- Perforated shelf for warming cabinets and cupboard bases (two-side operated for TL90) PNC 913236 ☐
- Side reinforced panel only in combination with side shelf, for freestanding units PNC 913260 ☐
- Shelf fixation for TL90 two-side operated PNC 913280 ☐
- Stainless steel dividing panel, 900x700mm, (it should only be used between Electrolux Professional thermaline Modular 90 and thermaline C90) PNC 913672 ☐
- Stainless steel side panel, 900x700mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions) PNC 913688 ☐