

Modular Cooking Range Line thermaline 90 - 900 mm Open base, 1 Side (H2) - H=550

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA#	



589311 (MC1ADAIOOO)

Open Base, one-side operated - H2

Short Form Specification

Item No.

900 mm wide open base compartment to store pots, pans, sheet pans, etc. with hygienic design and round edges. Internal frame for heavy duty sturdiness in stainless steel. Flat surface construction, easily cleanable.

IPX5 water resistant certification.

Configuration: One-side operated freestanding base, hygienic class H2.

Main Features

- Open base compartment for storage of pots, pans, sheet pans, etc.
- All major components may be easily accessed from the front.
- Unit to be placed below modular top appliances to store pots, pans, sheet pans, etc.

Construction


- Hygienic design of the open base compartment with large round edges.
- IPX5 water resistance certification.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in stainless steel.

APPROVAL:





Modular Cooking Range Line thermaline 90 - 900 mm Open base, 1 Side (H2) - H=550



Key Information:

External dimensions, Width: 589311 (MC1ADAIOOO) 900 mm External dimensions, Depth: 900 mm External dimensions, Height: 550 mm **Cupboard Cavity Dimensions** (width): 680 mm **Cupboard Cavity Dimensions** 330 mm (height): **Cupboard Cavity Dimensions** 740 mm (depth): Net weight: 25 kg





Modular Cooking Range Line thermaline 90 - 900 mm Open base, 1 Side (H2) - H=550

		Stainless steel side panel,	PNC 913689	
Optional AccessoriesStainless steel side panel,	PNC 912511	900x800mm, flush-fitting (it should only be used against the wall,		
900x800mm, freestanding		against a niche and in between		
 Stainless steel front kicking strip, 900mm width 	PNC 912599	Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that		
 Stainless steel side kicking strips left and right, freestanding, 900mm width 	PNC 912621	these have at least the same dimensions)		
 Stainless steel side kicking strips left and right, against the wall, 900mm width 	PNC 912624			
 Stainless steel side kicking strips left and right, back-to-back, 1810mm width 	PNC 912627			
 Stainless steel plinth, against wall, 900mm width 	PNC 912902			
 Stainless steel plinth, freestanding, 900mm width 	PNC 912921			
 Stainless steel panel, 900x800mm, against wall, left side 	PNC 913102			
 Stainless steel panel, 900x800mm, against wall, right side 	PNC 913106			
Back panel, 900x450mm, for bases one-side operated	PNC 913183			
Stainless steel side panel, left, H=800, flush	PNC 913224			
• Stainless steel side panel, left, H=800, flush	PNC 913225			
 Perforated shelf for warming cabinets and cupboard bases (one-side operated TL80-85-90 and two-side operated for TL80) 	PNC 913235			
 Side reinforced panel only in combination with side shelf, for freestanding units 	PNC 913259			
 Side reinforced panel only in combination with side shelf, for against the wall installations, left 	PNC 913268			
 Side reinforced panel only in combination with side shelf, for against the wall installations, right 	PNC 913270			
 Side reinforced panel only in combination with side shelf, for back-to-back installations, left 	PNC 913277			
 Side reinforced panel only in combination with side shelf, for back-to-back installation, right 	PNC 913278			
 Shelf fixation for TL80-85-90 one- side operated, TL80 two-side operated 	PNC 913283			
 Stainless steel dividing panel, 900x800mm, (it should only be used between Electrolux Professional thermaline Modular 90 and thermaline C90) 	PNC 913673			

