

Modular Cooking Range Line thermaline 90 - 800 mm Open base, GN conform, 1 Side (H2) - H=550

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



589317 (MC1BDAHOOO)

Open Base, one-side operated, GN - H2

Short Form Specification

Item No.

800 mm wide open base compartment to store pots, pans, sheet pans, etc. with hygienic design and round edges. Internal frame for heavy duty sturdiness in stainless steel. Flat surface construction, easily cleanable. Open storage space in the base accepts GN 1/1 containers.

IPX5 water resistant certification.

Configuration: One-side operated freestanding base, hygienic class H2.

Main Features

- All major components may be easily accessed from the front.
- Unit to be placed below modular top appliances to store pots, pans, sheet pans, etc

Construction

- IPX5 water resistance certification.
- Hygienic design of the open base compartment with large round edges.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Storage space in the base of the appliance that can accept GN1/1 containers.
- Internal frame for heavy duty sturdiness in stainless steel.

APPROVAL:





Modular Cooking Range Line thermaline 90 - 800 mm Open base, GN conform, 1 Side (H2) - H=550

Front 580 644 <u>7</u>8 Side 900 550 600 150 Top 800 900

Key Information:

External dimensions, Width:	
589317 (MC1BDAHOOO)	800 mm
External dimensions, Depth:	900 mm
External dimensions, Height:	550 mm
Cupboard Cavity Dimensions (width):	580 mm
Cupboard Cavity Dimensions (height):	330 mm
Cupboard Cavity Dimensions (depth):	740 mm
Net weight:	24 ka





Modular Cooking Range Line thermaline 90 - 800 mm Open base, GN conform, 1 Side (H2) - H=550

		Stainless steel side panel,	PNC 913689	
Optional Accessories		900x800mm, flush-fitting (it should	1110710007	
 Stainless steel side panel, 900x800mm, freestanding 	PNC 912511	only be used against the wall, against a niche and in between		
 Stainless steel front kicking strip, 800mm width 	PNC 912598	Electrolux Professional thermaline and ProThermetic appliances and		
 Stainless steel side kicking strips left and right, freestanding, 900mm width 	PNC 912621	external appliances - provided that these have at least the same dimensions)		
 Stainless steel side kicking strips left and right, against the wall, 900mm width 	PNC 912624			
 Stainless steel side kicking strips left and right, back-to-back, 1810mm width 	PNC 912627			
 Stainless steel plinth, against wall, 800mm width 	PNC 912901			
 Stainless steel plinth, freestanding, 800mm width 	PNC 912920			
Stainless steel panel, 900x800mm, against wall, left side	PNC 913102			
 Stainless steel panel, 900x800mm, against wall, right side 	PNC 913106			
 Back panel, 800x550mm, for bases one-side operated 	PNC 913182			
 Stainless steel side panel, left, H=800, flush 	PNC 913224			
 Stainless steel side panel, left, H=800, flush 	PNC 913225			
 Perforated shelf for warming cabinets and cupboard bases (one-side operated TL80-85-90 and two-side operated for TL80) 	PNC 913234			
 Side reinforced panel only in combination with side shelf, for freestanding units 	PNC 913259			
 Side reinforced panel only in combination with side shelf, for against the wall installations, left 	PNC 913268			
 Side reinforced panel only in combination with side shelf, for against the wall installations, right 	PNC 913270			
 Side reinforced panel only in combination with side shelf, for back-to-back installations, left 	PNC 913277			
 Side reinforced panel only in combination with side shelf, for back-to-back installation, right 	PNC 913278			
 Shelf fixation for TL80-85-90 one- side operated, TL80 two-side operated 	PNC 913281			
Stainless steel dividing panel, 900x800mm, (it should only be used between Electrolux Professional thermaline Modular	PNC 913673			



90 and thermaline C90)