

Modular Cooking Range Line thermaline 90 - 900 mm Passthrough open base, 2 Sides (H2) - H=550

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA #	



589325 (MC2ADCIOOO)

Passthrough Open Base, two-side operated - H2

Short Form Specification

Item No.

900 mm wide open passthrough base compartment to store pots, pans, sheet pans, etc. with hygienic design and round edges. Internal frame for heavy duty sturdiness in stainless steel. Flat surface construction, easily cleanable.

IPX5 water resistant certification.

Configuration: Two-side operated freestanding base, hygienic class H2.

Main Features

- Open base compartment for storage of pots, pans, sheet pans, etc.
- All major components may be easily accessed from the front.
- Unit to be placed below modular top appliances to store pots, pans, sheet pans, etc.

Construction


- Hygienic design of the open base compartment with large round edges.
- IPX5 water resistance certification.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in stainless steel.


APPROVAL:






Modular Cooking Range Line thermaline 90 - 900 mm Passthrough open base, 2 Sides (H2) - H=550







Key Information:

External	dimensions,	Width:
58932	5 (MC2ADCIO	OOO)

900 mm 900 mm External dimensions, Depth: External dimensions, Height: 550 mm

Cupboard Cavity Dimensions

680 mm

Cupboard Cavity Dimensions (height):

330 mm

Cupboard Cavity Dimensions

860 mm 25 kg

(depth): Net weight:





Modular Cooking Range Line thermaline 90 - 900 mm Passthrough open base, 2 Sides (H2) - H=550

Optional Accessories

• Stainless steel side panel, 900x800mm, freestanding	PNC 912511	
• Stainless steel front kicking strip, 900mm width	PNC 912599	
 Stainless steel side kicking strips left and right, freestanding, 900mm width 	PNC 912621	
 Stainless steel plinth, freestanding, 900mm width 	PNC 912921	
 Perforated shelf for warming cabinets and cupboard bases (two-side operated for TL90) 	PNC 913238	
 Side reinforced panel only in combination with side shelf, for freestanding units 	PNC 913259	
 Shelf fixation for TL90 two-side operated 	PNC 913284	
 Stainless steel dividing panel, 900x800mm, (it should only be used between Electrolux Professional thermaline Modular 90 and thermaline C90) 	PNC 913673	
Stainless steel side panel, 900x800mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions)	PNC 913689	

