

Modular Cooking Range Line thermaline 90 - 500 mm Passthrough open base, GN conform, 2 Sides (H2) -H=550



589329 (MC2BDCEOOO)

Passthrough Open Base, two-side operated, GN - H2

## **Short Form Specification**

#### Item No.

500 mm wide open passthrough base compartment to store pots, pans, sheet pans, etc. with hygienic design and round edges. Internal frame for heavy duty sturdiness in stainless steel. Flat surface construction, easily cleanable. Open storage space in the base accepts GN 1/1 containers.

IPX5 water resistant certification.

Configuration: Two-side operated freestanding base, hygienic class H2.

ITEM #	
MODEL #	
NAME #	
<u>SIS #</u>	
AIA #	

## **Main Features**

- All major components may be easily accessed from the front.
- Unit to be placed below modular top appliances to store pots, pans, sheet pans, etc.


## Construction

- IPX5 water resistance certification.
- Hygienic design of the open base compartment with large round edges.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Storage space in the base of the appliance that can accept GN1/1 containers.
- Internal frame for heavy duty sturdiness in stainless steel.

#### APPROVAL:

# Electrolux PROFESSIONAL

### Modular Cooking Range Line thermaline 90 - 500 mm Passthrough open base, GN conform, 2 Sides (H2) - H=550



CE

DNV-GL

## Key Information:

External dimensions, Width:	
589329 (MC2BDCEOOO)	500 mm
External dimensions, Depth:	900 mm
External dimensions, Height:	550 mm
Cupboard Cavity Dimensions (width):	340 mm
Cupboard Cavity Dimensions (height):	330 mm
Cupboard Cavity Dimensions (depth): Net weight:	860 mm 21 kg

Modular Cooking Range Line thermaline 90 - 500 mm Passthrough open base, GN conform, 2 Sides (H2) - H=550 The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.



# **Optional Accessories**

optional Accessories		
<ul> <li>Stainless steel side panel, 900x800mm, freestanding</li> </ul>	PNC 912511	
• Stainless steel front kicking strip, 500mm width	PNC 912595	
<ul> <li>Stainless steel side kicking strips left and right, freestanding, 900mm width</li> </ul>	PNC 912621	
<ul> <li>Stainless steel plinth, freestanding, 500mm width</li> </ul>	PNC 912917	
<ul> <li>Perforated shelf for warming cabinets and cupboard bases (two-side operated for TL90)</li> </ul>	PNC 913236	
<ul> <li>Side reinforced panel only in combination with side shelf, for freestanding units</li> </ul>	PNC 913259	
<ul> <li>Shelf fixation for TL90 two-side operated</li> </ul>	PNC 913280	
<ul> <li>Stainless steel dividing panel, 900x800mm, (it should only be used between Electrolux Professional thermaline Modular 90 and thermaline C90)</li> </ul>	PNC 913673	
• Stainless steel side panel, 900x800mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions)	PNC 913689	

