

Modular Cooking Range Line thermaline 90 - 600 mm Passthrough open base, GN conform, 2 Sides (H2) -H=550



589330 (MC2BDCFOOO)

Passthrough Open Base, two-side operated, GN - H2

Short Form Specification

Item No.

600 mm wide open passthrough base compartment to store pots, pans, sheet pans, etc. with hygienic design and round edges. Internal frame for heavy duty sturdiness in stainless steel. Flat surface construction, easily cleanable. Open storage space in the base accepts GN 1/1 containers.

IPX5 water resistant certification.

Configuration: Two-side operated freestanding base, hygienic class H2.

ITEM #	
MODEL #	
NAME #	
<u>SIS #</u>	
AIA #	

Main Features

- All major components may be easily accessed from the front.
- Unit to be placed below modular top appliances to store pots, pans, sheet pans, etc.


Construction

- IPX5 water resistance certification.
- Hygienic design of the open base compartment with large round edges.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Storage space in the base of the appliance that can accept GN1/1 containers.
- Internal frame for heavy duty sturdiness in stainless steel.

APPROVAL:

Electrolux PROFESSIONAL

Modular Cooking Range Line thermaline 90 - 600 mm Passthrough open base, GN conform, 2 Sides (H2) - H=550



Key Information:

600 mm
900 mm
550 mm
340 mm
330 mm
860 mm 22 kg

Modular Cooking Range Line thermaline 90 - 600 mm Passthrough open base, GN conform, 2 Sides (H2) - H=550 The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.



Optional Accessories

optional Accessiones		
 Stainless steel side panel, 900x800mm, freestanding 	PNC 912511	
• Stainless steel front kicking strip, 600mm width	PNC 912596	
 Stainless steel side kicking strips left and right, freestanding, 900mm width 	PNC 912621	
 Stainless steel plinth, freestanding, 600mm width 	PNC 912918	
 Perforated shelf for warming cabinets and cupboard bases (two-side operated for TL90) 	PNC 913236	
 Side reinforced panel only in combination with side shelf, for freestanding units 	PNC 913259	
Shelf fixation for TL90 two-side operated	PNC 913280	
• Stainless steel dividing panel, 900x800mm, (it should only be used between Electrolux Professional thermaline Modular 90 and thermaline C90)	PNC 913673	
• Stainless steel side panel, 900x800mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions)	PNC 913689	

