



Modular Cooking Range Line
thermaline 90 - Freestanding Electric
Multi Braiser, 2/1GN, 1 Side, Backsplash,
H=800

ITEM # _____
MODEL # _____
NAME # _____
SIS # _____
AIA # _____



589442
(MCADFBHDAO) Electric Multi Braiser, one-side operated with
backsplash, 2/1 GN

Configuration: Freestanding, One-side operated with
backsplash.

Short Form Specification

Item No. _____

Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth. Internal frame for heavy duty sturdiness in stainless steel. 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating. Multi-purpose cooking appliance which can be used to shallow fry, cook liquids or as a bain marie. 18 mm-thick stainless steel plated bottom, seamlessly welded to the chrome nickel steel well. Powerblock heating system for optimal temperature distribution, which can be set up to 280°C. Interior pan dimensions allows the use of GN containers. Large drain hole allows to drain the cooking juices into a large collector. All-round basin raised edges to protect against soil infiltration. Overheat protection switches off the supply in case of overheating. Standby function saves energy and quickly recovers maximum power. Metal knobs with embedded hygienic silicon "soft" grip enable easier handling and cleaning.
IPX5 water resistant certification.

APPROVAL: _____



Experience the Excellence
www.electroluxprofessional.com

Main Features

- Choice of one or two heating zones. An indicator lamp shows operating state of each zone.
- Large drain hole on cooking surface permits the draining of residual cooking juices into a large collector placed under the cooking surface.
- Multi purpose cooking appliance that can be used to shallow fry, cook liquids or even as a bain marie. Unit can be used for sautéing, poaching, steaming, simmering, stewing, braising, boiling and preparing white sauces.
- Overheat protection: the temperature sensor switches off the supply in case of overheating.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic "soft-touch" grip for easier handling and cleaning. The special design of the controls prevents infiltration of liquids or soil into vital components.
- Powerblock heating system for optimal temperature distribution.
- Handles are ergonomically designed with silicon "soft" grip for easy handling and cleaning.
- Raised edge all around the well to protect from infiltration of dirt from worktop.
- Temperature can be set up to a maximum of 280 °C.
- Interior dimensions of the well enables the use of GN containers.
- Large visible digital display manufactured in tempered glass to resist heat and chemicals, showing temperatures or power settings. The display also shows on/off status of the appliance and on/off status of the heating elements.

Construction

- An 18 mm thick stainless steel plated bottom is seamlessly welded into the chrome nickel steel well.
- Rounded corners and edges aid cleaning.
- Storage space in the base of the appliance that can accept GN1/1 containers.
- 2 mm top in 1.4301 (AISI 304).
- IPX5 water resistance certification.
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in stainless steel.

Sustainability

- Standby function for energy saving and fast recovery of maximum power.

Optional Accessories

- | | | |
|---|------------|--------------------------|
| • Lid for multi braisers, 2/1 GN | PNC 910621 | ☐ |
| • Connecting rail kit for appliances with backsplash, 900mm | PNC 912499 | ☐ |
| • Portioning shelf, 800mm width | PNC 912526 | ☐ |
| • Portioning shelf, 800mm width | PNC 912556 | ☐ |

- | | | |
|---|------------|--------------------------|
| • Folding shelf, 300x900mm | PNC 912581 | ☐ |
| • Folding shelf, 400x900mm | PNC 912582 | ☐ |
| • Fixed side shelf, 200x900mm | PNC 912589 | ☐ |
| • Fixed side shelf, 300x900mm | PNC 912590 | ☐ |
| • Fixed side shelf, 400x900mm | PNC 912591 | ☐ |
| • Stainless steel front kicking strip, 800mm width | PNC 912598 | ☐ |
| • Stainless steel side kicking strips left and right, against the wall, 900mm width | PNC 912624 | ☐ |
| • Stainless steel side kicking strips left and right, back-to-back, 1810mm width | PNC 912627 | ☐ |
| • Stainless steel plinth, against wall, 800mm width | PNC 912901 | ☐ |
| • Stainless steel plinth, freestanding, 800mm width | PNC 912920 | ☐ |
| • Connecting rail kit for appliances with backsplash: modular 90 (on the left) to ProThermatic tilting (on the right), ProThermatic stationary (on the left) to ProThermatic tilting (on the right) | PNC 912981 | ☐ |
| • Connecting rail kit for appliances with backsplash: modular 90 (on the right) to ProThermatic tilting (on the left), ProThermatic stationary (on the right) to ProThermatic tilting (on the left) | PNC 912982 | ☐ |
| • Back panel, 800x800mm, for units with backsplash | PNC 913026 | ☐ |
| • Stainless steel panel, 900x800mm, against wall, left side | PNC 913102 | ☐ |
| • Stainless steel panel, 900x800mm, against wall, right side | PNC 913106 | ☐ |
| • Endrail kit, flush-fitting, with backsplash, left | PNC 913117 | ☐ |
| • Endrail kit, flush-fitting, with backsplash, right | PNC 913118 | ☐ |
| • Scraper for smooth plates | PNC 913119 | ☐ |
| • Blades with rounded sides for scraper | PNC 913123 | ☐ |
| • Endrail kit (12.5mm) for thermaline 90 units with backsplash, left | PNC 913208 | ☐ |
| • Endrail kit (12.5mm) for thermaline 90 units with backsplash, right | PNC 913209 | ☐ |
| • U-clamping rail for back-to-back installations with backsplash (to be ordered as S-code) | PNC 913226 | ☐ |
| • Bottom plate for multibraiser 2/1 GN | PNC 913229 | ☐ |
| • Insert profile d=900 | PNC 913232 | ☐ |
| • Perforated shelf for warming cabinets and cupboard bases (one-side operated TL80-85-90 and two-side operated for TL80) | PNC 913234 | ☐ |
| • Energy optimizer kit 18A - factory fitted | PNC 913245 | ☐ |
| • Side reinforced panel only in combination with side shelf, for against the wall installations, left | PNC 913268 | ☐ |
| • Side reinforced panel only in combination with side shelf, for against the wall installations, right | PNC 913270 | ☐ |
| • Shelf fixation for TL80-85-90 one-side operated, TL80 two-side operated | PNC 913281 | ☐ |
| • Filter W=800mm | PNC 913665 | ☐ |



Electrolux
PROFESSIONAL

**Modular Cooking Range Line
thermaline 90 - Freestanding Electric Multi
Braiser, 2/1GN, 1 Side, Backsplash, H=800**

- Stainless steel dividing panel, 900x800mm, (it should only be used between Electrolux Professional thermaline Modular 90 and thermaline C90) PNC 913673 ☐
- Electric mains switch 25A 4mm² NM for modular H800 electric units (factory fitted) PNC 913676 ☐
- Drain stopper flush for multibraisers 2/1GN PNC 913681 ☐
- Stainless steel side panel, 900x800mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions) PNC 913689 ☐

Recommended Detergents

- C41 HI-TEMP RAPID DEGREASER, 1 pack of six 1 lt. bottles (trigger incl.) PNC 0S2292 ☐







Electrolux
PROFESSIONAL

Modular Cooking Range Line
thermaline 90 - Freestanding Electric Multi
Braiser, 2/1GN, 1 Side, Backsplash, H=800

Front




Side



EI = Electrical inlet (power)
EQ = Equipotential screw

Top



Electric

Supply voltage: 400 V/3N ph/50/60 Hz
Total Watts: 10.2 kW

Key Information:

Usable well dimensions (width): 630 mm
Usable well dimensions (height): 110 mm
Usable well dimensions (depth): 510 mm
Cooking Well Height: 110 mm
Well Capacity, Max: 22 lt
Working Temperature MIN: 80 °C
Working Temperature MAX: 280 °C
External dimensions, Width: 800 mm
External dimensions, Depth: 900 mm
External dimensions, Height: 800 mm
Storage Cavity Dimensions (width): 580 mm
Storage Cavity Dimensions (height): 330 mm
Storage Cavity Dimensions (depth): 740 mm
Net weight: 150 kg
Configuration: Rectangular;Fixed;With splashback

Sustainability

Current consumption: 14.7 Amps



Modular Cooking Range Line
thermaline 90 - Freestanding Electric Multi Braiser, 2/1GN, 1 Side,
Backsplash, H=800
The company reserves the right to make modifications to the products
without prior notice. All information correct at time of printing.

2025.10.13

Optional Accessories

• Lid for multi braisers, 2/1 GN	PNC 910621	☐	• Side reinforced panel only in combination with side shelf, for against the wall installations, left	PNC 913268	☐
• Connecting rail kit for appliances with backsplash, 900mm	PNC 912499	☐	• Side reinforced panel only in combination with side shelf, for against the wall installations, right	PNC 913270	☐
• Portioning shelf, 800mm width	PNC 912526	☐	• Shelf fixation for TL80-85-90 one-side operated, TL80 two-side operated	PNC 913281	☐
• Portioning shelf, 800mm width	PNC 912556	☐	• Filter W=800mm	PNC 913665	☐
• Folding shelf, 300x900mm	PNC 912581	☐	• Stainless steel dividing panel, 900x800mm, (it should only be used between Electrolux Professional thermaline Modular 90 and thermaline C90)	PNC 913673	☐
• Folding shelf, 400x900mm	PNC 912582	☐	• Electric mains switch 25A 4mm ² NM for modular H800 electric units (factory fitted)	PNC 913676	☐
• Fixed side shelf, 200x900mm	PNC 912589	☐	• Drain stopper flush for multibraisers 2/1GN	PNC 913681	☐
• Fixed side shelf, 300x900mm	PNC 912590	☐	• Stainless steel side panel, 900x800mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions)	PNC 913689	☐
• Fixed side shelf, 400x900mm	PNC 912591	☐			
• Stainless steel front kicking strip, 800mm width	PNC 912598	☐			
• Stainless steel side kicking strips left and right, against the wall, 900mm width	PNC 912624	☐			
• Stainless steel side kicking strips left and right, back-to-back, 1810mm width	PNC 912627	☐			
• Stainless steel plinth, against wall, 800mm width	PNC 912901	☐			
• Stainless steel plinth, freestanding, 800mm width	PNC 912920	☐			
• Connecting rail kit for appliances with backsplash: modular 90 (on the left) to ProThermetic tilting (on the right), ProThermetic stationary (on the left) to ProThermetic tilting (on the right)	PNC 912981	☐			
• Connecting rail kit for appliances with backsplash: modular 90 (on the right) to ProThermetic tilting (on the left), ProThermetic stationary (on the right) to ProThermetic tilting (on the left)	PNC 912982	☐			
• Back panel, 800x800mm, for units with backsplash	PNC 913026	☐			
• Stainless steel panel, 900x800mm, against wall, left side	PNC 913102	☐			
• Stainless steel panel, 900x800mm, against wall, right side	PNC 913106	☐			
• Endrail kit, flush-fitting, with backsplash, left	PNC 913117	☐			
• Endrail kit, flush-fitting, with backsplash, right	PNC 913118	☐			
• Scraper for smooth plates	PNC 913119	☐			
• Blades with rounded sides for scraper	PNC 913123	☐			
• Endrail kit (12.5mm) for thermaline 90 units with backsplash, left	PNC 913208	☐			
• Endrail kit (12.5mm) for thermaline 90 units with backsplash, right	PNC 913209	☐			
• U-clamping rail for back-to-back installations with backsplash (to be ordered as S-code)	PNC 913226	☐			
• Bottom plate for multibraiser 2/1 GN	PNC 913229	☐			
• Insert profile d=900	PNC 913232	☐			
• Perforated shelf for warming cabinets and cupboard bases (one-side operated TL80-85-90 and two-side operated for TL80)	PNC 913234	☐			
• Energy optimizer kit 18A - factory fitted	PNC 913245	☐			

Recommended Detergents

• C41 HI-TEMP RAPID DEGREASER, 1 pack of six 1 lt. bottles (trigger incl.)	PNC 0S2292	☐
--	------------	--------------------------