

Modular Cooking Range Line thermaline 90 - 40 lt Well Freestanding Gas Pasta Cooker, 1 Side with Backsplash, H=800

ITEM # _____
 MODEL # _____
 NAME # _____
 SIS # _____
 AIA # _____



589452 (MCKFFBDDPO)

40lt gas Pasta Cooker, one-side operated with backsplash

Short Form Specification

Item No.

Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth. Internal frame for heavy duty sturdiness in stainless steel. 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating. Appliance which can also be used to cook noodles of every kind, rice, dumplings and vegetables. Water basin in 1.4435 (AISI 316L) stainless steel, with automatic constant water level re-fill and water temperature regulation via sensors. Integrated drip tray to drain baskets. Compatible with automatic basket lifting system to facilitate lifting operations. Safety systems and automatic low-water level shut-off protect against overheating. All-round basin raised edges to protect against soil infiltration. Standby function saves energy and quickly recovers maximum power. Metal knobs with embedded hygienic silicon "soft" grip enable easier handling and cleaning. IPX5 water resistant certification.

Configuration: Freestanding, One-side operated with backsplash.

Main Features

- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic "soft-touch" grip for easier handling and cleaning. The special design of the controls prevents infiltration of liquids or soil into vital components.
- Provided with integrated drip zone on which baskets can be placed for draining purposes.
- In addition to cooking pasta, the appliance can be used for noodles of every kind, rice, dumplings and vegetables.
- Easy to clean basin with rounded corners.
- Raised edge all around the well to protect from infiltration of dirt from worktop.
- Safety systems protect against overtemperature and can be manually reset.
- Safety thermostat and thermostatic control.
- Electrical ignition powered by battery with thermocouple for added safety.

Construction

- 2 mm top in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Water basin in 1.4435 (AISI 316L) stainless steel is seamlessly welded into the top of the appliance.
- High efficiency burners in AISI 430 stainless steel with flame failure device.
- IPx4 water protection.
- Internal frame for heavy duty sturdiness in stainless steel.

Sustainability



- EnergyControl: unique feature for fine power adjustment to control boiling level and optimize energy consumption.

Optional Accessories

- Connecting rail kit for appliances PNC 912499 ☐
with backsplash, 900mm
- Portioning shelf, 400mm width PNC 912522 ☐
- Portioning shelf, 400mm width PNC 912552 ☐
- Folding shelf, 300x900mm PNC 912581 ☐

APPROVAL: _____

• Folding shelf, 400x900mm	PNC 912582	☐	• Endrail kit (12.5mm) for thermaline 90 units with backsplash, right	PNC 913209	☐
• Fixed side shelf, 200x900mm	PNC 912589	☐	• U-clamping rail for back-to-back installations with backsplash (to be ordered as S-code)	PNC 913226	☐
• Fixed side shelf, 300x900mm	PNC 912590	☐	• Side reinforced panel only in combination with side shelf, for against the wall installations, left	PNC 913268	☐
• Fixed side shelf, 400x900mm	PNC 912591	☐	• Side reinforced panel only in combination with side shelf, for against the wall installations, right	PNC 913270	☐
• Stainless steel front kicking strip, 400mm width	PNC 912594	☐	• Stainless steel dividing panel, 900x800mm, (it should only be used between Electrolux Professional thermaline Modular 90 and thermaline C90)	PNC 913673	☐
• Stainless steel side kicking strips left and right, against the wall, 900mm width	PNC 912624	☐	• Stainless steel side panel, 900x800mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions)	PNC 913689	☐
• Stainless steel side kicking strips left and right, back-to-back, 1810mm width	PNC 912627	☐	• Gas mainswitch for modular H800 gas units (factory fitted)	PNC 913698	☐
• Stainless steel plinth, against wall, 400mm width	PNC 912897	☐			
• Stainless steel plinth, freestanding, 400mm width	PNC 912916	☐			
• Connecting rail kit for appliances with backsplash: modular 90 (on the left) to ProThermetic tilting (on the right), ProThermetic stationary (on the left) to ProThermetic tilting (on the right)	PNC 912981	☐			
• Connecting rail kit for appliances with backsplash: modular 90 (on the right) to ProThermetic tilting (on the left), ProThermetic stationary (on the right) to ProThermetic tilting (on the left)	PNC 912982	☐			
• Back panel, 400x800mm, for units with backsplash	PNC 913022	☐			
• Stainless steel panel, 900x800mm, against wall, left side	PNC 913102	☐			
• Stainless steel panel, 900x800mm, against wall, right side	PNC 913106	☐			
• Endrail kit, flush-fitting, with backsplash, left	PNC 913117	☐			
• Endrail kit, flush-fitting, with backsplash, right	PNC 913118	☐			
• 3 ergonomic baskets for 40lt pasta cooker	PNC 913124	☐			
• 1 square basket for 40lt pasta cooker	PNC 913125	☐			
• 1 ergonomic basket for 40lt pasta cooker	PNC 913126	☐			
• False bottom for 40lt pasta cooker basket	PNC 913127	☐			
• 3 baskets 1/3 GN for 40lt pasta cooker	PNC 913128	☐			
• 2 baskets 1/2 GN for 40lt pasta cooker	PNC 913129	☐			
• 3 round baskets for 40lt pasta cooker	PNC 913130	☐			
• 6 round baskets for 40lt pasta cooker	PNC 913131	☐			
• Grid support for round baskets	PNC 913132	☐			
• Support frame for 6 round baskets	PNC 913133	☐			
• 1 basket 1/1 GN for 40lt pasta cooker, ProThermetic braising and pressure braising pans, GN compatible (to be combined with suspension frame)	PNC 913134	☐			
• Lid for 40lt pasta cooker	PNC 913149	☐			
• Endrail kit (12.5mm) for thermaline 90 units with backsplash, left	PNC 913208	☐			



2025.08.14