

Modular Cooking Range Line thermaline 90 - Full Module Freestanding Electric Fry Top, Mixed Plate, 1 Side, Backsplash, H=700

| ITEM # | |
|---------|---|
| | |
| MODEL # | |
| | |
| NAME # | |
| | |
| SIS # | |
| | |
| AIA# | |
| | _ |



589549 (MCHFEBHDAO)

Electric Fry Top with smooth and ribbed chrome Plate, one-side operated with backsplash

Short Form Specification

Item No.

Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth. Internal frame for heavy duty sturdiness in stainless steel. 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating. Chromium-plated mild steel cooking surface with non-stick finishing for optimal grilling. Stainless steel high splash guards on the rear and sides. Electrical control via thermocouples for precise temperature control and safety thermostat. Large drain hole allows draining of cooking juices into a large collector. Overheat protection switches off the supply in case of overheating. Metal knobs with embedded hygienic silicon "soft" grip enable easier handling and cleaning. IPX5 water resistant certification.

Configuration: Freestanding, One-side operated with backsplash.

Main Features

- Choice of one or two heating zones. An indicator lamp shows operating state of each zone.
- Large drain hole on cooking surface permits the draining of residual cooking juices into a large collector placed under the cooking surface.
- Overheat protection: the temperature sensor switches off the supply in case of overheating.
- Stainless steel high splash guards on the rear and sides of cooking surface.
- Units have separate controls for each half module of the cooking surface.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic "softtouch" grip for easier handling and cleaning.
 The special design of the controls prevents infiltration of liquids or soil into vital components.
- Large visible digital display manufactured in tempered glass to resist heat and chemicals, showing temperatures or power settings. The display also shows on/off status of the appliance and on/off status of the heating elements.
- Powerblock heating system for optimal temperature distribution.

Construction

- 2 mm top in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Cooking surface in chromium-plated mild steel with non-stick finishing for optimum grilling results.
- IPX5 water resistance certification.
- Internal frame for heavy duty sturdiness in stainless steel.
- Cooking surface 2/3 smooth and 1/3 ribbed.

Sustainability



 Standby function for energy saving and fast recovery of maximum power.

APPROVAL:






Modular Cooking Range Line thermaline 90 - Full Module Freestanding Electric Fry Top, Mixed Plate, 1 Side,Backsplash, H=700

| Optional Accessories | | Side reinforced panel only in combination with side shelf, for | _ |
|--|--------------------------|--|----------|
| Connecting rail kit for appliances | PNC 912499 | against the wall installations, right | |
| with backsplash, 900mm | DNIC 012524 | | |
| Portioning shelf, 800mm widthPortioning shelf, 800mm width | PNC 912526 PNC 912556 | □ side operated, TL80 two-side □ operated | |
| Folding shelf, 300x900mm | PNC 912530 | □ • Filter W=800mm PNC 913665 | 7 |
| Folding shelf, 400x900mm | PNC 912582 | • Stainless steel dividing panel, PNC 913672 | |
| • Fixed side shelf, 200x900mm | PNC 912589 | 900x700mm, (it should only be | _ |
| • Fixed side shelf, 300x900mm | PNC 912590 | used between Electrolux | |
| • Fixed side shelf, 400x900mm | PNC 912591 | 1 Totessional thermaline Modulal | |
| Stainless steel front kicking strip, 800mm width | PNC 912634 | • Stainless steel side panel, PNC 913688 | _ |
| Stainless steel side kicking strips left and right, against the wall, 900mm width | PNC 912660 | 900x700mm, flush-filting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline | |
| Stainless steel side kicking strip left and right, back-to-back, 1810mm width | | and ProThermetic appliances and external appliances – provided that these have at least the same dimensions) | |
| Stainless steel plinth, against wall, 800mm width | PNC 912939 | Recommended Detergents | |
| Connecting rail kit for appliances with backsplash: modular 90 (on the left) to ProThermetic tilting (on the right), ProThermetic stationary (on the left) to ProThermetic tilting (on the right) | PNC 912981 | C41 HI-TEMP RAPID DEGREASER, PNC 0S2292 I 1 pack of six 1 lt. bottles (trigger incl.) | ם |
| Connecting rail kit for appliances with backsplash: modular 90 (on the right) to ProThermetic tilting (on the left), ProThermetic stationary (on the right) to ProThermetic tilting (on the left) | PNC 912982 | | |
| • Back panel, 800x700mm, for units with backsplash | PNC 913013 | | |
| Stainless steel panel, 900x700mm, against wall, left side | PNC 913101 | | |
| Stainless steel panel, 900x700mm, against wall, right side | PNC 913105 | | |
| Endrail kit, flush-fitting, with backsplash, left | PNC 913117 | | |
| Endrail kit, flush-fitting, with backsplash, right | PNC 913118 | | |
| Scraper for smooth plates | PNC 913119 | | |
| Scraper for ribbed plates | PNC 913120 | | |
| • Endrail kit (12.5mm) for thermaline 90 units with backsplash, left | PNC 913208 | | |
| • Endrail kit (12.5mm) for thermaline 90 units with backsplash, right | PNC 913209 | | |
| U-clamping rail for back-to-back installations with backsplash (to be ordered as S-code) | PNC 913226 | | |
| Insert profile d=900 | PNC 913232 | | |
| Perforated shelf for warming cabinets and cupboard bases (one-side operated TL80-85-90 and two-side operated for TL80) | PNC 913234 | | |
| • Energy optimizer kit 24A - factory fitted | PNC 913246 | | |
| Side reinforced panel only in combination with side shelf, for against the wall installations, left | PNC 913267 | | |





Electric

Supply voltage: 400 V/3N ph/50/60 Hz

Total Watts: 15.3 kW

Key Information:

Cooking Surface Depth: 615 mm
Cooking Surface Width: 700 mm
Working Temperature MIN: 80 °C
Working Temperature MAX: 280 °C
External dimensions, Width: 800 mm
External dimensions, Depth: 900 mm
External dimensions, Height: 700 mm

Storage Cavity Dimensions

(width): 340 mm

Storage Cavity Dimensions

(height): Storage Cavity Dimensions

 (depth):
 740 mm

 Net weight:
 150 kg

On Base;One-Side

Configuration: Operated

Cooking surface type: half ribbed/ half smooth

Chromium Plated mild

330 mm

Cooking surface - material: steel mirror

Sustainability

Current consumption: 22.1 Amps

