

Modular Cooking Range Line thermaline 90 - 4 Zone Electric Solid Top on Oven, 1 Side-Ecotop H=700- Marine

ITEM # _____
 MODEL # _____
 NAME # _____
 SIS # _____
 AIA # _____



589884 (MCLMEAJ8DM)

Electric Solid Top, 4 zones,
 ecoTop coating, one-side
 operated - Marine, on Oven

Short Form Specification

Item No.

Unit constructed according to DIN 18860_2 with 20 mm drop nose top. Internal frame for heavy duty sturdiness in stainless steel. 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating. ECOTOP model with a 20 mm thick steel cooking surface with heat retaining coating. 4 independently controlled heating zones with 2 electronic sensors per zone for temperature surface control and 8 power levels. Rapid plate heat up, continuously ready to use. Overheat protection switches off the supply in case of overheating. Standby function saves energy and quickly recovers maximum power. Metal knobs with embedded hygienic silicon "soft" grip enable easier handling and cleaning. Electric static oven base with 40 mm thick oven door and ribbed enamelled steel base plate. Constructed according to 1.4301 (AISI 304). Oven chamber with 2 levels of runners for 2/1 GN shelves to enable simultaneous and faster cooking. Heavy duty thermostat with temperature range up to 300°C, electronic sensor for precise temperature control and manual humidity control in the cooking chamber. Upper heating element can also be used for grilling, with or without ventilating mode. Flat surface construction, easily cleanable. Overheat protection switches off the supply in case of overheating. Standby function saves energy and quickly recovers maximum power. Metal knobs and oven handles ergonomically designed with embedded hygienic silicon "soft" grip enable easier handling and cleaning. IPX5 water resistance certification.

Main Features

- 4 heating zones independently controlled.
- Rapid heat up of the plate and continuously ready for use.
- Overheat protection: a temperature sensor switches off the supply in case of overheating.
- Pans can easily be moved from one area to another without lifting.
- Wide rounded cleaning zone around the plates for easier cleaning.
- 40 mm thick oven door for heat insulation.
- All major components may be easily accessed from the front.
- ECOTOP model has a 20 mm thick steel DIN 1.7335 nickel coated cooking surface.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic "soft-touch" grip for easier handling and cleaning. The special design of the controls prevents infiltration of liquids or soil into vital components.
- Large visible digital display manufactured in tempered glass to resist heat and chemicals, showing temperatures or power settings. The display also shows on/off status of the appliance and on/off status of the heating elements.
- Cooking plate and base joint profile guarantee against soil infiltration.
- Handles are ergonomically designed with silicon "soft" grip for easy handling and cleaning.
- Oven chamber to have 2 levels of runners to accommodate 2/1 GN trays and ribbed enamelled steel base plate.
- The upper heating element of the oven can also be used for grilling.
- Manual control of humidity in cooking chamber.
- Electronic sensor for precise temperature control.
- Two electronic sensors per zone to control surface temperature and to protect cooking plate from overheating.
- 8 power levels.
- Unit constructed according to DIN 18860_2 with 70 mm recessed plinth.
- Oven temperature up to 300 °C

Construction

- 2 mm top in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top.
- IPX5 water resistance certification.
- Internal frame for heavy duty sturdiness in stainless steel.

APPROVAL: _____





Electrolux
PROFESSIONAL

**Modular Cooking Range Line
thermaline 90 - 4 Zone Electric Solid Top
on Oven, 1 Side-Ecotop H=700-Marine**

Sustainability

- Standby function for energy saving and fast recovery of maximum power.

Included Accessories

- 1 of Grid, chromium plated, for ovens PNC 910652
2/1 GN

Optional Accessories


- | | | |
|---|------------|--------------------------|
| • Baking sheet 2/1 GN for ovens | PNC 910651 | ☐ |
| • Bottom steel plate 2/1 GN for fire
clay plate 800x900 with baking
oven | PNC 910655 | ☐ |
| • Fire clay plate 2/1 GN for ovens | PNC 910656 | ☐ |
| • Connecting rail kit, 900mm | PNC 912502 | ☐ |
| • Stainless steel side panel,
900x700mm, freestanding | PNC 912512 | ☐ |
| • Portioning shelf, 1000mm width | PNC 912528 | ☐ |
| • Portioning shelf, 1000mm width | PNC 912558 | ☐ |
| • Folding shelf, 300x900mm | PNC 912581 | ☐ |
| • Folding shelf, 400x900mm | PNC 912582 | ☐ |
| • Fixed side shelf, 200x900mm | PNC 912589 | ☐ |
| • Fixed side shelf, 300x900mm | PNC 912590 | ☐ |
| • Fixed side shelf, 400x900mm | PNC 912591 | ☐ |
| • Endrail kit, flush-fitting, left | PNC 913111 | ☐ |
| • Endrail kit, flush-fitting, right | PNC 913112 | ☐ |
| • Endrail kit (12.5mm) for thermaline 90
units, left | PNC 913202 | ☐ |
| • Endrail kit (12.5mm) for thermaline 90
units, right | PNC 913203 | ☐ |
| • Stainless steel side panel, left, H=700 | PNC 913222 | ☐ |
| • Stainless steel side panel, right,
H=700 | PNC 913223 | ☐ |
| • T-connection rail for back-to-back
installations without backsplash (to
be ordered as S-code) | PNC 913227 | ☐ |
| • Endrail kit, (12.5mm), for back-to-
back installation, left | PNC 913251 | ☐ |
| • Endrail kit, (12.5mm), for back-to-
back installation, right | PNC 913252 | ☐ |
| • Endrail kit, flush-fitting, for back-to-
back installation, left | PNC 913255 | ☐ |
| • Endrail kit, flush-fitting, for back-to-
back installation, right | PNC 913256 | ☐ |
| • Side reinforced panel only in
combination with side shelf, for
freestanding units | PNC 913260 | ☐ |
| • Side reinforced panel only in
combination with side shelf, for
back-to-back installations, left | PNC 913275 | ☐ |
| • Side reinforced panel only in
combination with side shelf, for
back-to-back installation, right | PNC 913276 | ☐ |
| • Filter W=1000mm | PNC 913666 | ☐ |
| • Stainless steel dividing panel,
900x700mm, (it should only be used
between Electrolux Professional
thermaline Modular 90 and
thermaline C90) | PNC 913672 | ☐ |
| • Stainless steel side panel,
900x700mm, flush-fitting (it should
only be used against the wall,
against a niche and in between
Electrolux Professional thermaline
and ProThermatic appliances and
external appliances - provided that
these have at least the same
dimensions) | PNC 913688 | ☐ |




Electrolux
PROFESSIONAL

**Modular Cooking Range Line
thermaline 90 - 4 Zone Electric Solid Top
on Oven, 1 Side-Ecotop H=700-Marine**

Front




Side



EI = Electrical inlet (power)
EQ = Equipotential screw

Top



Electric

Supply voltage: 440 V/3 ph/50/60 Hz
Electrical power, max: 21 kW

Key Information:

Working Temperature MIN: 100 °C
Working Temperature MAX: 450 °C
External dimensions, Width: 1000 mm
External dimensions, Depth: 900 mm
External dimensions, Height: 700 mm
Net weight: 258 kg
Configuration: On Oven; One-Side Operated
Front Plates Power: 4 - 4 kW
Back Plates Power: 4 - 4 kW
Solid top usable surface (width): 820 mm
Solid top usable surface (depth): 720 mm

Sustainability

Current consumption: 33.5 Amps