



Electrolux
PROFESSIONAL

Modular Cooking Range Line
thermaline 90 - 800 mm Cupboard base
with 2 doors, GN conform, 1 Side (H2) -
H=450 (Marine)

ITEM # _____
MODEL # _____
NAME # _____
SIS # _____
AIA # _____



589906 (MC1JCAHOOM)

Cupboard Base with 2
doors, one-side operated,
GN - H3, Marine feet

Short Form Specification

Item No. _____

800 mm wide cupboard base with 2 doors with hygienic design and round edges. Internal frame for heavy duty sturdiness in stainless steel. Flat surface construction, easily cleanable. Cupboard storage space accepts GN1/1 containers. IPX5 water resistant certification. Configuration: One-side operated freestanding base, hygienic class H2.

Main Features

- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Unit constructed according to DIN 18860_2 with 70 mm recessed plinth.
- Cupboard compartment for storage of pots, pans, sheet pans etc.

Construction

- IPX5 water resistance certification.
- Hygienic design of the base cupboard with large round edges.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Storage space in the base of the appliance accepts GN1/1 containers.
- Internal frame for heavy duty sturdiness in stainless steel.

Optional Accessories

- Stainless steel side panel, 900x700mm, freestanding PNC 912512 ☐
- Stainless steel front kicking strip, 800mm width PNC 912634 ☐
- Stainless steel side kicking strip left and right, freestanding, 900mm width PNC 912657 ☐
- Stainless steel side kicking strips left and right, against the wall, 900mm width PNC 912660 ☐
- Stainless steel side kicking strip left and right, back-to-back, 1810mm width PNC 912663 ☐
- Stainless steel plinth, against wall, 800mm width PNC 912939 ☐
- Stainless steel plinth, freestanding, 800mm width PNC 912958 ☐
- Stainless steel panel, 900x700mm, against wall, left side PNC 913101 ☐
- Stainless steel panel, 900x700mm, against wall, right side PNC 913105 ☐
- Back panel, 800x450mm, for bases one-side operated PNC 913167 ☐
- Stainless steel side panel, left, H=700 PNC 913222 ☐
- Stainless steel side panel, right, H=700 PNC 913223 ☐

APPROVAL: _____



Experience the Excellence
www.electroluxprofessional.com


- | | | |
|---|------------|--------------------------|
| • Perforated shelf for warming cabinets and cupboard bases (one-side operated TL80-85-90 and two-side operated for TL80) | PNC 913234 | ☐ |
| • Side reinforced panel only in combination with side shelf, for freestanding units | PNC 913260 | ☐ |
| • Side reinforced panel only in combination with side shelf, for against the wall installations, left | PNC 913267 | ☐ |
| • Side reinforced panel only in combination with side shelf, for against the wall installations, right | PNC 913269 | ☐ |
| • Side reinforced panel only in combination with side shelf, for back-to-back installations, left | PNC 913275 | ☐ |
| • Side reinforced panel only in combination with side shelf, for back-to-back installation, right | PNC 913276 | ☐ |
| • Shelf fixation for TL80-85-90 one-side operated, TL80 two-side operated | PNC 913281 | ☐ |
| • Stainless steel dividing panel, 900x700mm, (it should only be used between Electrolux Professional thermaline Modular 90 and thermaline C90) | PNC 913672 | ☐ |
| • Stainless steel side panel, 900x700mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions) | PNC 913688 | ☐ |




Electrolux
PROFESSIONAL

Modular Cooking Range Line
thermaline 90 - 800 mm Cupboard base with 2
doors, GN conform, 1 Side (H2) - H=450
(Marine)


Front



Side



Top



Key Information:

External dimensions, Width:	
589906 (MC1JCAHOOM)	800 mm
External dimensions, Depth:	900 mm
External dimensions, Height:	450 mm
Cupboard Cavity Dimensions (width):	580 mm
Cupboard Cavity Dimensions (height):	330 mm
Cupboard Cavity Dimensions (depth):	715 mm
Net weight:	30 kg



Modular Cooking Range Line
thermaline 90 - 800 mm Cupboard base with 2 doors, GN conform, 1
Side (H2) - H=450 (Marine)
The company reserves the right to make modifications to the products
without prior notice. All information correct at time of printing.

2025.09.09