

Modular Cooking Range Line thermaline 90 - 2-Burner Gas Top, 1 Side, Backsplash (Town Gas)

ITEM #		
MODEL #		
MODEL #		
NAME #		
SIS #		
AIA #		



593307 (MCGDABEOVO)

2-Burner gas Top, one-side operated with backsplash, town gas

Short Form Specification

Item No.

Unit constructed according to DIN 18860_2 with 20 mm drop nose top. Internal frame for heavy duty sturdiness in stainless steel. 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating. 2 gas burners with optimized combustion, flame failure device, thermocouple safety hand valve and protected pilot flame. Triple ring "flower" flame burners with anti-clogging design. Manual gas valves allow precise flame intensity control. Large pan support in cast iron with long center fins for various pan sizes. Deep flat spillage tray with rounded corners and drain hole. Metal knobs with embedded hygienic silicon "soft" grip enable easier handling and cleaning.

IPX4 water resistant certification.

Configuration: One-side operated top with backsplash. The base needs to be supplied by the factory. Please include appropriate base.

Main Features

- Flame failure device on each burner protects against gas leakage when accidental extinguishing of the flame occurs.
- Large sized pan support in cast iron with long center fins to allow the use of the largest down to the smallest pans.
- Manual gas valves allow precise control of the flame intensity between high and low positions.
- Pans can easily be moved from one area to another without lifting.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic "softtouch" grip for easier handling and cleaning. The special design of the controls prevents infiltration of liquids or soil into vital components.
- Burners with optimized combustion. Triple ring flower flame burners with anti-clogging design.
- Patented Flower Flame burners that adjust to the size and form of the cookware (Patent EP2708813B1 and related family).

Construction


- Each burner equipped with thermocouple safety hand valve and protected pilot flame.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in 1.4301 (AISI 304).
- IPx4 water protection.
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top.
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth.

APPROVAL:





Modular Cooking Range Line thermaline 90 - 2-Burner Gas Top, 1 Side, Backsplash (Town Gas)



Gas	
Gas Power: Gas Type Option:	17 kW
Gas Inlet:	1/2"
Key Information:	
External dimensions, Width:	500 mm
External dimensions, Depth:	900 mm
External dimensions, Height:	250 mm
Net weight:	41 kg
Configuration:	One-Side Operated;Top
Front Burners Power:	8.5 - kW
Back Burners Power:	8.5 - 0 kW
Back Burners Dimension - mm	Ø 70
Front Burners Dimension -	Ø 70





Modular Cooking Range Line thermaline 90 - 2-Burner Gas Top, 1 Side, Backsplash (Town Gas)

Optional Accessories

o paronar / tocosocrico		
 Connecting rail kit for appliances with backsplash, 900mm 	PNC 912499	
Portioning shelf, 500mm width	PNC 912523	
Portioning shelf, 500mm width	PNC 912553	
• Folding shelf, 300x900mm	PNC 912581	
•		
• Folding shelf, 400x900mm	PNC 912582	
 Fixed side shelf, 200x900mm 	PNC 912589	
 Fixed side shelf, 300x900mm 	PNC 912590	
 Fixed side shelf, 400x900mm 	PNC 912591	
Connecting rail kit for appliances with backsplash: modular 90 (on the left) to ProThermetic tilting (on the right), ProThermetic stationary (on the left) to ProThermetic tilting (on the right)	PNC 912981	
Connecting rail kit for appliances with backsplash: modular 90 (on the right) to ProThermetic tilting (on the left), ProThermetic stationary (on the right) to ProThermetic tilting (on the left)	PNC 912982	
 Back panel, 500x700mm, for units with backsplash 	PNC 913010	
Back panel, 500x800mm, for units with backsplash	PNC 913023	
Endrail kit, flush-fitting, with backsplash, left	PNC 913117	
Endrail kit, flush-fitting, with backsplash, right	PNC 913118	
• Endrail kit (12.5mm) for thermaline 90 units with backsplash, left	PNC 913208	
• Endrail kit (12.5mm) for thermaline 90 units with backsplash, right	PNC 913209	
 U-clamping rail for back-to-back installations with backsplash (to be ordered as S-code) 	PNC 913226	
• Insert profile d=900	PNC 913232	
• Stainless steel side panel (12,5mm),	PNC 913636	\Box
900x400mm, left side, wall mounted		_
 Stainless steel side panel (12,5mm), 900x400mm, right side, wall mounted 	PNC 913637	
Stainless steel side panel, 900x400mm, flush-fitting, left side, wall mounted	PNC 913638	
Stainless steel side panel,	DNC 017/70	
900x400mm, flush-fitting, right side,	PNC 913639	_
 900x400mm, flush-fitting, right side, wall mounted Wall mounting kit top - TL85/90 - Factory Fitted 	PNC 913649	_

