

Modular Cooking Range Line thermaline 90 - Full Module Gas Fry Top, 1 Side with Backsplash (Town Gas)

ITEM #	
MODEL "	
MODEL #	
NAME #	
CIC "	
SIS #	
AIA#	



593321 (MCHMABHOVO) Gas Fry Top with smooth chrome Plate, oneside operated with backsplash, town gas

593325 (MCHNABHOVO) Gas Fry Top with ribbed chrome Plate, oneside operated with backsplash, town gas

Short Form Specification

Item No.

Unit constructed according to DIN 18860_2 with 20 mm drop nose top. Internal frame for heavy duty sturdiness in stainless steel. 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating. Chromium-plated mild steel cooking surface with non-stick finishing for optimal grilling. Stainless steel high splash guards on the rear and sides. Features safety thermostat, thermostatic control and led indication of pilot flame. Electrical ignition powered by battery with thermocouple for added safety. Large drain hole allows draining of cooking juices into a large collector. Overheat protection switches off the supply in case of overheating. Metal knobs with embedded hygienic silicon "soft" grip enable easier handling and cleaning.

IPX5 water resistant certification.

Configuration: One-side operated top with backsplash.

Main Features

- Choice of one or two heating zones. An indicator lamp shows operating state of each zone.
- Large drain hole on cooking surface permits the draining of residual cooking juices into a large collector placed under the cooking surface.
- Overheat protection: the temperature sensor switches off the supply in case of overheating.
- Stainless steel high splash guards on the rear and sides of cooking surface.
- Units have separate controls for each half module of the cooking surface.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic "soft-touch" grip for easier handling and cleaning. The special design of the controls prevents infiltration of liquids or soil into vital components.
- Safety thermostat and thermostatic control.
- Electrical ignition powered by battery with thermocouple for added safety.
- Led indication of pilot flame

Construction

- 2 mm top in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in 1.4301 (AISI 304).
- Cooking surface in chromium-plated mild steel with non-stick finishing for optimum grilling results.
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top.
- Cooking surface to be completely smooth or completely ribbed.
- IPx4 water protection.

APPROVAL:





Modular Cooking Range Line thermaline 90 - Full Module Gas Fry Top, 1 Side with Backsplash (Town Gas)

Optional Accessories	DV 10 010 / 00	Gas	
 Connecting rail kit for appliances with backsplash, 900mm 	PNC 912499	Gas Power:	20 kW
 Portioning shelf, 800mm width 	PNC 912526	Gas Type Option: Gas Inlet:	1/2"
 Portioning shelf, 800mm width 	PNC 912556		1/2
 Folding shelf, 300x900mm 	PNC 912581	Key Information:	
 Folding shelf, 400x900mm 	PNC 912582	Cooking Surface Depth:	615 mm
 Fixed side shelf, 200x900mm 	PNC 912589	Cooking Surface Width:	700 mm
 Fixed side shelf, 300x900mm 	PNC 912590	Working Temperature MIN:	110 °C
 Fixed side shelf, 400x900mm 	PNC 912591	Working Temperature MAX:	270 °C
 Connecting rail kit for appliances with backsplash: modular 90 (on the left) to 	PNC 912981	External dimensions, Width:	800 mm
ProThermetic tilting (on the right),	1	External dimensions, Depth:	900 mm
ProThermetic stationary (on the left) to		External dimensions, Height:	250 mm
ProThermetic tilting (on the right)		Net weight:	120 kg
 Connecting rail kit for appliances with backsplash: modular 90 (on the right) 	PNC 912982	Configuration:	One-Side Operated;Top
to ProThermetic tilting (on the left),		Cooking surface type:	
ProThermetic stationary (on the right)		593321 (MCHMABHOVO)	Smooth
to ProThermetic tilting (on the left)		593325 (MCHNABHOVO)	Ribbed
Back panel, 800x700mm, for units with	PNC 913013		Chromium Plated mild
backsplashBack panel, 800x800mm, for units with	PNC 913026	Cooking surface - material:	steel mirror
backsplashEndrail kit, flush-fitting, with	PNC 913117		
backsplash, left • Endrail kit, flush-fitting, with	PNC 913118		
backsplash, right			
 Scraper for smooth plates (only for 593321) 	PNC 913119		
 Scraper for ribbed plates (only for 593325) 	PNC 913120		
 Endrail kit (12.5mm) for thermaline 90 units with backsplash, left 	PNC 913208		
 Endrail kit (12.5mm) for thermaline 90 units with backsplash, right 	PNC 913209		
 U-clamping rail for back-to-back installations with backsplash (to be ordered as S-code) 	PNC 913226		
 Insert profile d=900 	PNC 913232		
 Stainless steel side panel (12,5mm), 900x400mm, left side, wall mounted 	PNC 913636		
 Stainless steel side panel (12,5mm), 900x400mm, right side, wall mounted 	PNC 913637		
 Stainless steel side panel, 900x400mm, flush-fitting, left side, wall mounted 	PNC 913638		
 Stainless steel side panel, 900x400mm, flush-fitting, right side, wall mounted 	PNC 913639		
 Wall mounting kit top - TL85/90 - Factory Fitted 	PNC 913652		
Recommended Detergents			
C41 HI-TEMP RAPID DEGREASER, 1 pack of six 1 lt. bottles (trigger incl.)	PNC 0S2292		



Modular Cooking Range Line thermaline 90 - Full Module Gas Fry Top, 1 Side with Backsplash (Town Gas)



