

Modulare Großküchengeräteserie 700XP Freestanding Gas Boiling Pan 60lt direct heat

Technisches Datenblatt

ARTIKEL #

MODELL #

NAME #

SIS #

AIA #



371271 (E7BSGHDNF0)

Gas-Kochkessel, 60 l, direkte
Beheizung

Hauptmerkmale

Main Features

- Kettle is suitable to cook, sauté or poach all kinds of produce.
- Produce is uniformly heated in the base and side walls of the kettle by a direct heating system.
- Pressed cooking vessel and lid in 316 AISI Stainless steel.
- Robust burners in stainless steel with flame failure device, protected pilot light and optimized combustion.
- Appliance is IPX4 water resistance certified.
- Solenoid valve to refill with hot and cold water.
- Safety valve avoids overpressure of the steam in the jacket.
- No overshooting of cooking temperatures, fast reaction.
- Large capacity drain tap enables precise portioning of the discharged food, especially small quantities.
- Firmly fitting cover to reduce cooking time and save energy costs.
- Ergonomic: unique ratio vessel diameter and height; depth facilitates stirring and gentle food handling.
- Discharge tube and tap are very easy to clean from outside.
- Smooth large surfaces, easy access for cleaning.
- Exterior panels in Stainless Steel with Scotch Brite finish.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- Unit delivered with four 50 mm legs in stainless steel as standard (all round Stainless steel kick plates as option).

Konstruktion

- Robuste Edelstahlbrenner mit Flammenwächter, geschützter Zündflamme und optimierter Verbrennung.
- Einteilige tiefgezogene 1,5 mm dicke Deckplatte aus Edelstahl.
- IPx4-Wasserschutz.
- Die Tanks sind aus zwei Teilen geschweißt: Der Seitenmantel besteht aus AISI 304, der Boden aus AISI 316L und die Deckel aus AISI 304.

Nachhaltigkeit




- Geschlossenes Heizsystem - keine Energieverschwendung
- Festsitzender Deckel reduziert die Kochzeit und spart Energiekosten.

Optionales Zubehör


- Verbindungs-/Dichtungsmittel PNC 206086 ☐
- Rückstromverhinderer, 150 mm Ø PNC 206132 ☐

Genehmigung: _____

Front




Seite



CWI = Kaltwasserzulauf
 D = Ablauf
 EI = Elektroanschluss
 G = Gasanschluss

HWI = Warmwasserzulauf

oben



Elektrisch

Netzspannung: 230 V/1N ph/50 Hz
 Gesamt-Watt: 0.1 kW

Gas

Gasleistung: 14 kW
 Standardgasart: Erdgas
 Gasart, Option: Flüssiggas
 Gaszufuhr: $\frac{1}{2}''$

Schlüsselinformation

No clearance needed on rear sides of unit if wall is of non combustible type. If wall is combustible, minimum 50 mm wall clearance should be maintained.

Tiegel-Nutzhalt: 60 lt
 Durchmesser runder Kochkessel: 420 mm
 Nettogewicht: 95 kg
 Versandgewicht: 84 kg
 Versandhöhe: 1140 mm
 Versandlänge: 820 mm
 Versandtiefe: 860 mm
 Versandvolumen: 0.8 m³
 Zertifizierungsgruppe: N7PG