Electrolux PROFESSIONAL

Coffee System TANGO ACEMTSELF, 1 group fullautomatic machine



602561 (TANGOACEMTSELF) Full-automatic machine, 1 group, 220x40 ml espresso cup/hr, 6,5 liter steam/coffee boiler, 1x1,7 kg coffee hopper for beans, 0,8-1,5 kg hopper for powder, hot water

Short Form Specification

Item No.

The super automatic multi-products Tango® ACE MT takes advantage of the reliability, usability and exceptional extraction quality that has established the reputation of the TANGO® range, and the ability to work with powdered products such as cocoa. In its Self version, the Tango® ACE comes with lockers for beans and powder products hoppers and waste coffee drawer, it has no steam outlet neither ground coffee box for security reason. The Tango® ACE MT Self version is ideal for using in all self-service areas with its self-explanatory 7" color touch screen user interface easy to use.

Delivery capacity: Espresso 40ml: 220 cups/h Lungo 100ml: 150 cups/h Hot water: 30 L/h

ITEM #		
MODEL #		
NAME #	 	
<u>SIS #</u>		
AIA #		

Main Features

- 1 group full-automatic machine with self service configuration.
- 6.5 liter steam/coffee boiler.
- Auto cleaning program.
- Programmable hot water.
- Tango[®] ACE comes with lockers for beans and powder products hoppers and waste coffee drawer, it has no steam outlet neither ground coffee box for security reason.
- The super automatic multi-products Tango® ACE MT takes advantage of the reliability, usability and exceptional extraction quality that has established the reputation of the TANGO® range, and the ability to work with powdered products such as cocoa.
- The Tango[®] ACE MT Self version is ideal for using in all self-service areas with its selfexplanatory 7" color touch screen user interface easy to use.
- Delivery capacity: Espresso 40ml: 220 cups/h Lungo 100ml: 150 cups/h Hot water: 30 L/h

Construction

- 1 x 1,7 kg coffee hopper & coffee grinder + (0,8 at 1,5) kg hopper for powder.
- LCD Touchscreen.
- PID (proportional-integral-derivative) Temperature control: a precise controller algorithm system that gives consistency and accuracy to brewing temperature management system.
- Safety locks.


Optional Accessories

- TANGO hotel/breakfast service PNC 871022 kit
- Coffee ground direct discharge PNC 871023 chute
- Raised feet kit
 PNC 871041

APPROVAL:



Coffee System TANGO ACEMTSELF, 1 group fullautomatic machine



Coffee System TANGO ACEMTSELF, 1 group full-automatic machine

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.



Electric		
Supply voltage: Electrical power max: Plug type:	400 V/3N ph/50 Hz 5.2 kW Cable without plug	
Water:		
Cold water temperature (min/max):	5 / 60 °C	
Key Information:		
Net weight: Shipping volume:	91 kg 0.69 m³	
Sustainability		
Current consumption:	7.5 Amps	

