

Modular Cooking Range Line 900XP Automatic Basket Lifting System - 200 mm

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____


206353 (LIFT9E)

 Automatic programmable
 Basket Lifting System for 40lt
 Pasta Cookers, 3 lifters

Short Form Specification

Item No. _____


Unit to be 900XP Automatic programmable basket lifting system for 24,5lt pasta cookers, with 3 lifters. 200 mm wide basket lifting system with 3 stainless steel basket supports to lift one 1/3 basket per lifter (baskets are optional, to be ordered separately). Unit shall be placed on either side of the pasta cooker or in combination with a second automatic lifting unit on the opposite side to provide lifting for 6 single portion square baskets. The unit shall feature programmability and automatic lifting function to guarantee repeatability of the cooking cycle.

APPROVAL: _____

Main Features

- The electronic programmability and automatic lifting of the baskets make this unit a must for any kitchen wanting to standardize their cooking procedures.
- Programmability and automatic lifting function guarantee repeatability of the cooking cycle, thus ensuring the same high quality of the food time after time due to the automation of the entire cooking process.
- Unit can be used also in "manual mode" by pushing a button to lower and raise baskets.
- Possibility to memorize up to 9 cooking times via digital control, which can be assigned independently to the single basket support.
- Easy operation, automatic basket lifting can be activated through push button function.
- 200 mm wide automatic basket lifting system with 3 stainless steel basket supports, to provide lifting for one 1/3 basket per lifter (baskets are optional accessories to be ordered separately).
- Unit may be placed on either side of the pasta cooker or in combination with a second automatic lifting unit on the opposite side to provide lifting for 6 single portion square baskets

Front



Electric

Supply voltage:

206353 (LIFT9E)

230 V/1 ph/50/60 Hz

Total Watts:

0.2 kW

Key Information:


External dimensions, Width: 200 mm

External dimensions, Depth: 930 mm

External dimensions, Height: 850 mm

Net weight: 40 kg

Side



EI = Electrical inlet (power)
 EQ = Equipotential screw

Top

