## ITEM # **MODEL** #

NAME #

<u>SIS</u> #

### **Coffee System** PrecisionBrew single warmer shuttle brewer

**GRINDMASTER** 



600623 (PBC1W2CE)

PrecisionBrew single warmer shuttle brewer (shuttle not included)

# **Short Form Specification**

### Item No.

Single PrecisionBrew warmer shuttle brewer that brews into 5.7lt vacuum shuttle. Shuttles® sensor prevents brewing when server is not in place. Digitally controlled with PrecisionBrew™ Technology. Advanced touchscreen digital interface simplifies and streamlines brewing and operation.

### **Main Features**

AIA#

- · Sensor prevents brewing when shuttle is not in place.
- · Machine knows if brew basket is installed.
- Digitally controlled with PrecisionBrew<sup>™</sup> Technology.
- Intuitive, icon-driven touchscreen digital interface simplifies and streamlines brewing and operation.
- · Interactive diagnostics through touch display.
- Reimagined modern design for PrecisionBrew™: single and double sightglass models brew into 5.7 L warmer Shuttle(s)®.

### Construction

• 12.1 L heating tank per brew head indipendent water tanks ensure consistent temperature and volume.


### **Included Accessories**


• 1 of Plastic brew basket for PNC 870040 coffee


# PrecisionBrew single warmer shuttle brewer

**APPROVAL:** 

# GRINDMASTER Coffee System PrecisionBrew single warmer shuttle brewer







### **Electric**

Supply voltage:

600623 (PBC1W2CE) 230 V/1 ph/50/60 Hz

**Electrical power max.:** 2.8 kW

### **Key Information:**

External dimensions, Width:	232 mm
External dimensions, Depth:	486 mm
External dimensions, Height:	852 mm
Net weight:	20 kg
Shipping weight:	24 kg
Shipping height:	890 mm
Shipping width:	360 mm
Shipping depth:	650 mm
Shipping volume:	0.21 m <sup>3</sup>

Coffee System PrecisionBrew single warmer shuttle brewer

