GRINDMASTE

PrecisionBrew vacuum shuttle double brewer with integrated

GRINDMASTER

Coffee System PrecisionBrew vacuum shuttle double brewer with integrated base

IIEW #		
MODEL #		
NAME #		
SIS #		
ΔΙΛ #		



600626 (PBC2V2CE)

PrecisionBrew double vacuum shuttle brewer with integrated base for vacuum shuttle (not included) without stand

Short Form Specification

Item No.

Double PrecisionBrew vacuum shuttle brewer that brews into 5.7lt vacuum shuttle. Shuttles® sensor prevents brewing when server is not in place. Digitally controlled with PrecisionBrew™ Technology. Advanced touchscreen digital interface simplifies and streamlines brewing and operation.

Main Features

- Reimagined modern design for PrecisionBrew™: single and double sightglass models brew into 5.7 L vacuum Shuttle (s)®.
- Sensor prevents brewing when shuttle is not in place.
- · Machine knows if brew basket is installed.
- Digitally controlled with PrecisionBrew™ Technology.
- Intuitive, icon-driven touchscreen digital interface simplifies and streamlines brewing and operation.
- · Interactive diagnostics through touch display.

Construction

 12.1 L heating tank per brew head indipendent water tanks ensure consistent temperature and volume.

Included Accessories

2 of Plastic brew basket for coffee
 PNC 870040

Optional Accessories

• 5.7 It Vacuum shuttle without stand PNC 600633 $\ \square$

APPROVAL:

Tee System
integrated
base

GRINDMASTER

Coffee System PrecisionBrew vacuum shuttle double brewer with integrated base

Front [18'] 457mm Side [33 7/16*] 850mm ΕI [8 15/16'] 227mm WI [8 1/8'] Top [15 1/2'] 394mm WI ΕI _[3 5/16*] 84mm **E**

Electric

Supply voltage:

600626 (PBC2V2CE) 230 V/1 ph/50/60 Hz

Electrical power max.: 2.8 kW

Key Information:

External dimensions, Width:	552 mm
External dimensions, Depth:	486 mm
External dimensions, Height:	889 mm
Net weight:	36 kg
Shipping weight:	43 kg
Shipping height:	890 mm
Shipping width:	550 mm
Shipping depth:	490 mm



