

### Chest Freezer Sliding Glass Lid Novelty Freezer 38" Long



## **Short Form Specification**

#### <u>ltem No.</u>

Glass lids top chest freezer with internal structure in painted steel and external structure in textured painted steel. Fan cooler condenser and 1/6 HP compressor. Freezer baskets and internal digital control with cabinet temperature display. Locking lids and key to protect the contents in the unit. Equipped with NEMA 5-15P plug.

Basket and NSF®-Certified Temperature Gauge.

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		

## **Main Features**

- Fan cooled condenser to cope with heavy duty conditions
- Mechanical control panel with adjustable temperature
- Basket Durable and reliable for safety in food storage (1 basket included).
- NSF®-Certified Temperature Gauge Durable and reliable for safety in food storage.

# Construction

- Heavy Duty Castors
- Static Condenser
- Tempered glass sliding lids
- Exterior and Interior finish in white painted steel
- Locking lids and key protect the contents of the unit

# **Sustainability**

- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- CFC and HCFC free (ecological refrigerant type: R600a).

# **Optional Accessories**

 Basket for Glass Lid Chest Freezer 16.26x8.66x9.53 in (413x220x242 mm)

**APPROVAL:** 

Kelvinator Commercial www.kelvinatorcommercial.com



# Chest Freezer Sliding Glass Lid Novelty Freezer 38" Long



Electric		
Supply voltage: Electrical power, max: Plug type:	115 V/1 ph/60 Hz 0.3 kW USA NEMA 5-15P	
Capacity:		
Gross capacity:	14.9 cu.feet	
Key Information:		
Internal dimensions, Height: External dimensions, Width: External dimensions, Depth: External dimensions, Height: Internal Dimensions (depth): Internal Dimensions (width): Net weight: Shipping width: Shipping height: Shipping volume: Approvals	26 " (660.4 mm) 37 13/16" (960 mm) 20 11/16" (525 mm) 33 1/16" (840 mm) 15 " / (381 mm) 32 " / (812.8 mm) 88 lbs (40 kg) 23 1/32" (585 mm) 34 5/8" (880 mm) 88 lbs (40 kg) 18.27 ft <sup>3</sup> (0.52 m <sup>3</sup> ) ETL C&USETL SANITATION	
<b>Refrigeration Data</b>		
Operating temperature min.: Compressor power: Operating temperature max.:	-18.4 °F 1/6 hp 3.2 °F	
Sustainability		
Current consumption: Refrigerant type: GWP Index: Refrigerant weight:	1.2 Amps R600a 3 25 g	



(W I I (ET) 5xear 15A 125V NEMA 5-15P Intertek Intertek

Chest Freezer Sliding Glass Lid Novelty Freezer 38" Long

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

Kelvinator Commercial is a pending or registered trademark of Electrolux Consumer Products, Inc., and is used under a license from Electrolux Consumer Products, Inc.