

COMMERCIAL

Refrigeration Equipment 1-Door Pizza Prep Table 48 " Long 6-1/3 Pan



Short Form Specification

ltem No.

1-door pizza refrigerated preparation table. Exterior back panel and exterior bottom panel in galvanized steel, exterior side and top panel in 430 stainless steel; interior back, side panels and bottom panel in 304 stainless steel, worktop in 304 stainless steel. Built-in refrigeration unit and an insulated lid to maintain food freshness. Fin & Tube Condenser improves performance in high-temperature environments. Automatic Defrost Cooling System to provide worry-free performances. Full-depth cutting board of 47.3x17.7x0.5 in. Control panel, Vinyl-Coated Steel adjustable shelves, removable door gaskets and self-closing door with 90-degree stay-open feature.

Temperature range: +33/+41°F.

R290 gas in the refrigeration circuit.

ETL Safety and Sanitation certifications.

3/5 Years warranty

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA #	

Main Features

- External temperature display.
- Removable gasket for easy cleaning operations.
- Fin & Tube Condenser improves performance in high temperature environments.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.
- Full Depth cutting board.
- Cabinet completely insulated with high density polyurethane for low environmental impact.
- Heavy duty Vinyl coated steel shelves.

Construction

- Holds 6 1/3 pans.
- · Heavy duty casters.
- Insulated lid maintains food freshness.
- Pre-wired heavy duty power cord.
- · Heavy duty door hinges.
- Magnetic gasket removable without tools for easy cleaning.

Sustainability

- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) CFC and HCFC free.

Optional Accessories

• Drawer Kit for KCHPT50.6 PNC 880694 (738252) Pizza Table

APPROVAL:

Part of

Kelvinator Commercial www.kelvinatorcommercial.com



Æ

_____))

35.1"[892mm]

14.9"[378mm

58.7"[1490mm]

47.2"[1200mm]

1084

28"[710mm]

16.6"[421mm]

13.1"[334mm] 1.8"[45mm]

530.2mm

EI = Electrical connection

58mm

2.5"[63mm]

35.8"[910mm

EL

2.3"[58mm

1.2" 30mm

41.3[°][1050mm] 28.3"[720mm]

5,9"[150m

47.4"[1203mm]

000000000 000000000

Side

26.8[680mm]

Top

3.9"[100mm]

2.3"[58mm]

"[50mn

Omm

27"[685.8mm]

29.9" [760mm

000000000

Refrigeration Equipment 1-Door Pizza Prep Table 48 " Long 6-1/3 Pan

115 V/1 ph/60 Hz

0.72 kW

NEMA 5-15

1 - 638x634

12 cu.feet

Electric Front Supply voltage: **Electrical power, max:** Plug type:

Capacity: Number and type of grids (included):

Gross capacity:

Key Information:

Warranty: 3 / 5 years Door hinges: Left External dimensions, Width: 47 3/8" (1203 mm) External dimensions, Depth: 32 1/4" (820 mm) External dimensions, Height: 41 5/16" (1050 mm) Number and type of doors: 1 Full Internal Dimensions (depth): 27 1/2" / (698.5 mm) Internal Dimensions (height): 23 "/(584.2 mm) Internal Dimensions (width): 25 1/2" / (647.7 mm) Shipping height: 44 1/2" (1130 mm) Shipping weight: 291 lbs (132 kg) Shipping volume: 43.24 ft³ (1.22 m³) Type of external material: Stainless Steel Type of internal material: 304 AISI Approvals ETL C&US;ETL SANITATION

Refrigeration Data

Condenser type: Fin & tube 32 °F Operating temperature min.: **Compressor power:** 1/3 hp **Operating temperature max.:** 41 °F Defrost type: Auto Defrost

Sustainability

Current consumption:	5 Amps
Refrigerant type:	R290
GWP Index:	3
Refrigerant weight:	105 g



Refrigeration Equipment 1-Door Pizza Prep Table 48" Long 6-1/3 Pan

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

Kelvinator Commercial is a pending or registered trademark of Electrolux Consumer Products, Inc., and is used under a license from Electrolux Consumer Products, Inc.