

Refrigeration Equipment 3-Door Pizza Prep Table 94 " Long 12-1/3 Pan

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



738254 (KCHPT92.12)

3-Door Pizza Prep Table 94
" Long 12-1/3 Pan

Short Form Specification

Item No. _____

3-door pizza refrigerated preparation table. Exterior back panel and exterior bottom panel in galvanized steel, exterior side and top panel in 430 stainless steel; interior back, side panels and bottom panel in 304 stainless steel, worktop in 304 stainless steel. Built-in refrigeration unit and an insulated lid to maintain food freshness. Fin & Tube Condenser improves performance in high-temperature environments. Automatic Defrost Cooling System to provide worry-free performances. Full-depth cutting board of 91.81 x 17.7x0.5 in. Control panel, Vinyl-Coated Steel adjustable shelves, removable door gaskets and self-closing door with 90-degree stay-open feature.

Temperature range: +33/+41°F.

R290 gas in the refrigeration circuit.

ETL Safety and Sanitation certifications.

3/5 Years warranty

Main Features

- External temperature display.
- Removable gasket for easy cleaning operations.
- Fin & Tube Condenser improves performance in high temperature environments.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.
- Full Depth cutting board.
- Cabinet completely insulated with high density polyurethane for low environmental impact.
- Automatic Defrost Cooling System provides worry-free performance.
- Heavy duty Vinyl coated steel shelves.
- Adjustable shelves for flexible storage
- Removable rubber bumper guards for airflow spacing and shock absorption
- Side-mounted refrigeration system improves airflow, reduces heat buildup behind the unit, and allows easy service access
- Integrated polyethylene (PE) cutting board included for food-safe, durable prep surface

Construction

- Stainless steel interior and exterior, durable and easy to clean for daily commercial use.
- Holds 12 1/3 pans.
- Insulated lid maintains food freshness.
- Heavy duty casters.
- Pre-wired heavy duty power cord.
- Heavy duty door hinges.
- Self-closing door with 90-degree stay-open feature.
- Magnetic gasket removable without tools for easy cleaning.
- Stainless steel worktop, durable functionality


Sustainability

- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) - CFC and HCFC free.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- 58 mm insulation for energy saving

Optional Accessories

- Drawers Kit for L/R section of 94" Pizza PNC 880696
- Prep Table
- Drawer Kit for Center Section of 94" Pizza PNC 880697
- " Pizza Prep Table

APPROVAL: _____



Electric

Supply voltage:	115 V/1 ph/60 Hz
Electrical power, max:	0.93 kW
Plug type:	NEMA 5-15

Capacity:

Gross capacity:	32 cu.feet
-----------------	------------

Key Information:

Number and type of grids (included):	3 - Vinyl-Coated steel
Number and type of pans (included):	12 - Plastic
Number and type of cutting board (included):	1 - Polyethylene (PE)
Warranty:	3 / 5 years
Door hinges:	1 Left+2 Right
External dimensions, Width:	94 3/16" (2393 mm)
External dimensions, Depth:	32 1/4" (820 mm)
External dimensions, Height:	41 5/16" (1050 mm)
Number and type of doors:	3 Full
Internal Dimensions (depth):	27 1/2" / (698.5 mm)
Internal Dimensions (height):	23 " / (584.2 mm)
Internal Dimensions (width):	72 1/2" / (1841.5 mm)
Shipping height:	44 1/2" (1130 mm)
Shipping weight:	551 lbs (250 kg)
Shipping volume:	84.07 ft ³ (2.38 m ³)
Type of external material:	Stainless Steel
Type of internal material:	304 AISI
Approvals	ETL C&US;ETL SANITATION

Refrigeration Data

Condenser type:	Fin & tube
Operating temperature min.:	32 °F
Compressor power:	1/2 hp
Operating temperature max.:	41 °F
Defrost type:	Auto Defrost

Sustainability

Current consumption:	5.5 Amps
Refrigerant type:	R290
GWP Index:	3
Refrigerant weight:	105 g