

Refrigeration Equipment 1-Door Refrigerated Under Counter 27" Long

ITEM #		
MODEL #		
NAME #		
SIS #		
•		
AIA #		



738263 (KCHUC27R)

1-Door Refrigerated Under Counter 27" Long

Short Form Specification

Item No.

1-door refrigerator counter top, 35.5 inches tall, with exterior back panel, exterior bottom panel, and exterior top panel in galvanized steel, exterior side panel in 430 stainless steel; interior back, top and bottom panels in 304 stainless steel. Fin & tube condenser to improve the performances in high temperature environments. Automatic Defrost Cooling System and temperature control. Vinyl heavy duty adjustable, easy to handle and clean shelves. On-site reversible door feature for units with serial number 24020014 or later. External temperature display.

R600a gas in refrigeration circuit. ETL Safety and Sanitation certified.

3/5 Years warranty.

Main Features

- External temperature display.
- Removable gasket for easy cleaning operations.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.
- Heavy duty Vinyl coated steel shelves.
- Cabinet completely insulated with high density polyurethane for low environmental impact.

Construction

- Stainless steel interior and exterior, durable and easy to clean for daily commercial use.
- Self-closing door with 90-degree stay-open feature.
- Heavy duty casters.
- Pre-wired heavy duty power cord.
- Heavy duty door hinges.
- Magnetic gasket removable without tools for easy cleaning.

Sustainability


- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- CFC and HCFC free (ecological refrigerant type: R600a).


Optional Accessories

- 1 ADJUSTABLE FOOT PNC 206445 □
- Drawer Kit for 27" Undercounter PNC 880614 🖵



Refrigeration Equipment 1-Door Refrigerated Under Counter 27" Long





Electric

Supply voltage:

738263 (KCHUC27R) 115 V/1 ph/60 Hz

Electrical power, max: 0.16 kW

Plug type: USA NEMA 5-15P

Capacity:

Gross capacity: 6.5 cu.feet

Key Information:

Door hinges:Right SideExternal dimensions, Width:27 3/4" (705 mm)External dimensions, Depth:29 15/16" (760 mm)External dimensions, Height:35 1/2" (902 mm)

Number and type of doors: 1 Full

Internal Dimensions (depth): 22 13/16" / (580 mm)
Internal Dimensions (height): 23 1/2" / (597 mm)
Internal Dimensions (width): 22 1/4" / (565 mm)
Shipping height: 38 3/16" (970 mm)
Shipping weight: 165 lbs (75 kg)
Shipping volume: 20.41 ft³ (0.58 m³)

Number and type of grids

(included): 1 - Vinyl-Coated Steel

Type of external material: Stainless Steel
Type of internal material: Polystyrene
Warranty: 3 / 5 years

ENERGY STAR;ETL C&US;ETL

Approvals SANITATION

Refrigeration Data

Current absorbed: 1.5 Amps
Compressor power: 1/10 hp
Operating temperature min.: 32 °F
Operating temperature max.: 41 °F
Condenser type: Fin & tube
Defrost type: Auto Defrost

Sustainability

Refrigerant type: R600a GWP Index: 3 Refrigerant weight: 70 g

energy STAR

Electrical connection









Refrigeration Equipment 1-Door Refrigerated Under Counter 27" Long