

COMMERCIAL

#### Refrigeration Equipment 3-Solid Door Back Bar Refrigerator Black 73" Long



#### **Short Form Specification**

#### Item No.

3-door Back bar refrigerator. Exterior back and bottom panels in galvanized steel, top panel in 304 stainless steel and exterior side panels in painted steel; interior back, side, and top panels in 430 stainless steel, interior bottom panel and worktop in 304 stainless steel. Fin & tube condenser to improve the performances in high temperature environments. Automatic Defrost Cooling System and temperature control. Heavy duty adjustable shelves and stayopen self-closing doors.

R290 gas in refrigeration circuit.

ETL Safety and Sanitation certified.

3/5 Years warranty.

ITEM #	
MODEL #	
NAME #	
<u>SIS #</u>	
AIA #	

### **Main Features**

- External digital temperature display.
- External temperature display.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Locking doors.
- · Heavy duty Vinyl coated steel shelves.
- Cabinet completely insulated with high density polyurethane for low environmental impact.

### Construction

- Lockable door.
- Self-closing door with 90-degree stay-open feature.
- Pre-wired heavy duty power cord.
- · Heavy duty door hinges.
- Magnetic gasket removable without tools for easy cleaning.

#### **Sustainability**

- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) CFC and HCFC free.

APPROVAL:

Part of

Kelvinator Commercial www.kelvinatorcommercial.com



36.2"-920mm 33.5" 850mm 5"-217mm 20.2"-512,7mm

73.1"-1856mm 71.9"-1826mm

F

42.4"-1077mm

24.4"-620mm 21.6"-550mm

**EI** = Electrical connection

20.2"-512,7mm

# Refrigeration Equipment 3-Solid Door Back Bar Refrigerator Black 73" Long

## -----

nt Electric	
Supply voltage: 738271 (KCHBB72S) Electrical power, max: Plug type: Capacity: Gross capacity: Key Information:	115 V/1 ph/60 Hz 0.31 kW USA NEMA 5-15P
Gross capacity:	20.8 cu feet
Key Information:	2010 0011001
Door hinges: External dimensions, Width: External dimensions, Depth: External dimensions, Depth: External dimensions, Height: Number and type of doors: Internal Dimensions (depth): Internal Dimensions (height): Internal Dimensions (width): Shipping height: Shipping weight: Shipping volume: Number and type of grids (included): Type of external material: Type of internal material: Warranty: Approvals	1 Left+2 Right 73 1/16" (1856 mm) 24 7/16" (620 mm) 36 1/4" (920 mm) 3 Full 20 " / (508 mm) 28 " / (711.2 mm) 60 " / (1524 mm) 41 5/16" (1050 mm) 337 lbs (153 kg) 47.8 ft <sup>3</sup> (1.35 m <sup>3</sup> ) 6 - Vinyl-Coated Steel Black Prepainted Steel Black Prepainted Steel Stainless Steel 3 / 5 years ETL C&USETL SANITATION
<b>Refrigeration Data</b>	
Compressor power: Operating temperature min.: Operating temperature max.: Condenser type: Defrost type:	1/5 hp 32 °F 41 °F Fin & tube Auto Defrost
Sustainability	
Current consumption: Refrigerant type: GWP Index: Refrigerant weight:	3 Amps R290 3 130 g



Refrigeration Equipment 3-Solid Door Back Bar Refrigerator Black 73" Long

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

Kelvinator Commercial is a pending or registered trademark of Electrolux Consumer Products, Inc., and is used under a license from Electrolux Consumer Products, Inc.