

## Refrigeration Equipment 3-Solid Door Back Bar Refrigerator Black 73" Long

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		
AIA #		



738271 (KCHBB72S)

3-Solid Door Back Bar Refrigerator Black 73" Long

## **Short Form Specification**

#### Item No.

3-door Back bar refrigerator. Exterior back and bottom panels in galvanized steel, top panel in 304 stainless steel and exterior side panels in painted steel; interior back, side, and top panels in 430 stainless steel, interior bottom panel and worktop in 304 stainless steel. Fin & tube condenser to improve the performances in high temperature environments. Automatic Defrost Cooling System and temperature control. Heavy duty adjustable shelves and stayopen self-closing doors.

R290 gas in refrigeration circuit.

ETL Safety and Sanitation certified.

3/5 Years warranty.

### **Main Features**

- External digital temperature display.
- External temperature display.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- · Locking doors.
- Heavy duty Vinyl coated steel shelves.
- Cabinet completely insulated with high density polyurethane for low environmental impact.

### Construction


- Lockable door.
- Self-closing door with 90-degree stay-open feature.
- Pre-wired heavy duty power cord.
- Heavy duty door hinges.
- Magnetic gasket removable without tools for easy cleaning.

# Sustainability


- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) - CFC and HCFC free.



# Refrigeration Equipment 3-Solid Door Back Bar Refrigerator Black 73" Long



Side



El = Electrical connection

#### **Electric**

**Supply voltage:** 115 V/1 ph/60 Hz **Electrical power, max:** 0.31 kW

Plug type: USA NEMA 5-15P

### **Capacity:**

Gross capacity: 20.8 cu.feet

### **Key Information:**

Number and type of grids

(included): 6 - Vinyl-Coated Steel

Warranty: 3 / 5 years

Door hinges: 1 Left+2 Right

External dimensions, Width: 73 1/16" (1856 mm)

External dimensions, Depth: 24 7/16" (620 mm)

External dimensions, Height: 36 1/4" (920 mm)

Number and type of doors: 3 Full

Internal Dimensions (depth): 20 "/(508 mm) Internal Dimensions (height): 28 "/(711.2 mm) Internal Dimensions (width): 60 "/(1524 mm) Shipping height: 41 5/16" (1050 mm) Shipping weight: 337 lbs (153 kg) Shipping volume: 47.8 ft3 (1.35 m3) Type of external material: **Black Prepainted Steel** Type of internal material: Stainless Steel

Approvals ETL C&US;ETL SANITATION

### **Refrigeration Data**

Condenser type: Fin & tube
Operating temperature min.: 32 °F
Compressor power: 1/5 hp
Operating temperature max.: 41 °F
Defrost type: Auto Defrost

### **Sustainability**

Current consumption:3 AmpsRefrigerant type:R290GWP Index:3Refrigerant weight:130 g







