

COMMERCIAL

Refrigeration Equipment 3-Glass Door Back Bar Refrigerator Black 73" Long



738274 (KCHBB72G)

3-Glass Door Back Bar Refrigerator Black 73" Long

Short Form Specification

Item No.

3-glass door Back bar refrigerator. Exterior back and bottom panels in galvanized steel, top panel in 304 stainless steel and exterior side panels in painted steel; interior back, side, and top panels in 430 stainless steel, interior bottom panel and worktop in 304 stainless steel. Fin & tube condenser to improve the performances in high temperature environments. Automatic Defrost Cooling System and temperature control. Heavy duty adjustable shelves and stayopen self-closing doors.

R290 gas in refrigeration circuit.

ETL Safety and Sanitation certified.

3/5 Years warranty.

ITEM #	
MODEL #	
NAME #	
<u>SIS #</u>	
AIA #	

Main Features

- External digital temperature display.
- External temperature display.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Locking doors.
- · Heavy duty Vinyl coated steel shelves.
- Cabinet completely insulated with high density polyurethane for low environmental impact.

Construction

- Lockable door.
- Self-closing door with 90-degree stay-open feature.
- Pre-wired heavy duty power cord.
- · Heavy duty door hinges.
- Magnetic gasket removable without tools for easy cleaning.

Sustainability

- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) CFC and HCFC free.

APPROVAL:

Part of


Kelvinator Commercial www.kelvinatorcommercial.com



5"-217mm

Refrigeration Equipment 3-Glass Door Back Bar Refrigerator Black 73" Long

Electric	
Supply voltage: Electrical power, max: Plug type:	115 V/1 ph/60 Hz 0.31 kW USA NEMA 5-15P
Capacity:	
Gross capacity:	20.8 cu.feet
Key Information:	
Number and type of grids (included): Warranty: Door hinges: External dimensions, Width: External dimensions, Depth: External dimensions, Height: Number and type of doors: Internal Dimensions (depth): Internal Dimensions (depth): Internal Dimensions (width): Shipping height: Shipping weight: Shipping volume: Type of external material: Type of internal material: Approvals	6 - Vinyl-Coated Steel 3 / 5 years 1 Left+2 Right 73 1/16" (1856 mm) 24 7/16" (620 mm) 36 1/4" (920 mm) 3 Glass 20 " / (508 mm) 28 " / (711.2 mm) 60 " / (1524 mm) 41 5/16" (1050 mm) 397 lbs (180 kg) 47.8 ft ³ (1.35 m ³) Black Prepainted Steel Stainless Steel ETL C&USETL SANITATION
Refrigeration Data	
Condenser type: Operating temperature min.: Compressor power: Operating temperature max.: Defrost type:	Fin & tube 32 °F 1/5 hp 41 °F Auto Defrost
Sustainability	
Current consumption: Refrigerant type: GWP Index: Refrigerant weight:	3 Amps R290 3 130 g



73.1"-1856mm 71.9"-1826mm

20.2"-512,7mm

ĸ

ы

20.2"-512,7mm



Refrigeration Equipment 3-Glass Door Back Bar Refrigerator Black 73" Long

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

Kelvinator Commercial is a pending or registered trademark of Electrolux Consumer Products, Inc., and is used under a license from Electrolux Consumer Products, Inc.

٦

20.2"-512,7mm