

#### COMMERCIAL

# Refrigeration Equipment 2-Drawer Refrigerator Under Counter 27" Long

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



738290 (KCHUC27.2DR)

2-Drawer Refrigerator Under Counter 27" Long

# **Short Form Specification**

#### Item No.

2-drawer refrigerator counter top with exterior back panel in aluminium, exterior bottom panel in galvanized steel, exterior side and top panel in 430 stainless steel; interior back, top and bottom panels in 304 stainless steel.

Fin & tube condenser to improve the performances in high temperature environments. Automatic Defrost Cooling System and temperature control. Vinyl heavy duty adjustable, easy to handle and clean shelves. External temperature display.

R600a gas in refrigeration circuit. ETL Safety and Sanitation certified. 3/5 Years warranty.

## **Main Features**

- External temperature display.
- · Removable gasket for easy cleaning operations.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.
- · Heavy duty Vinyl coated steel shelves.
- Cabinet completely insulated with high density polyurethane for low environmental impact.

### Construction


- Stainless steel interior and exterior, durable and easy to clean for daily commercial use.
- Heavy duty casters.
- · Pre-wired heavy duty power cord.
- Magnetic gasket removable without tools for easy cleaning.
- · Heavy duty drawer runners.


### **Sustainability**

- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- CFC and HCFC free (ecological refrigerant type: R600a).




# Refrigeration Equipment 2-Drawer Refrigerator Under Counter 27" Long





**EI** = Electrical connection



**Electric** 

**Front** 

Side

Top

Supply voltage:

**738290 (KCHUC27.2DR)** 115 V/1 ph/60 Hz

Electrical power, max: 0.2 kW

Plug type: USA NEMA 5-15P

**Key Information:** 

Capacity (Cu.Ft.) 27

External dimensions, Width: 27 3/4" (705 mm)
External dimensions, Depth: 29 15/16" (760 mm)
External dimensions, Height: 35 1/2" (902 mm)

Number and type of doors:

Internal Dimensions (depth):22 13/16"Internal Dimensions (height):23 1/2"Internal Dimensions (width):22 1/4"

 $\begin{array}{lll} \textbf{Shipping height:} & 38\ 3/16"\ (970\ mm) \\ \textbf{Shipping weight:} & 209\ lbs\ (95\ kg) \\ \textbf{Shipping volume:} & 20.41\ ft^3\ (0.58\ m^3) \\ \end{array}$ 

Number and type of grids

(included): 1 - Vinyl-Coated Steel

Type of external material: Stainless Steel
Type of internal material: 304 AISI
Warranty: 3 / 5 years

**Refrigeration Data** 

Compressor Horsepower: 1/6

Operating temperature min.: ISO 9001 °F
Operating temperature max.: 41 °F
Condenser type: Fin & tube
Defrost type: Auto Defrost

**Sustainability** 

Current consumption:1.5 AmpsRefrigerant type:R600aRefrigerant weight:70 g











