

### Refrigeration Equipment 2-Door Under Counter Refrigerator 61" Long

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



738291 (KCHUC60R)

2-Door Under Counter Refrigerator 61" Long

### **Short Form Specification**

Item No.

2-door refrigerator counter top, 35.5 inches tall, with exterior back panel, exterior bottom panel, and exterior top panel in galvanized steel, exterior side panel in 430 stainless steel; interior back, top and bottom panels in 304 stainless steel. Fin & tube condenser to improve the performances in high temperature = environments. Automatic Defrost Cooling System and temperature control. Vinyl heavy duty adjustable, easy to handle and clean shelves. External temperature display.

R600a gas in refrigeration circuit. ETL Safety and Sanitation certified.

3/5 Years warranty.

### **Main Features**

- External temperature display.
- Removable gasket for easy cleaning operations.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.
- Heavy duty Vinyl coated steel shelves.
- Cabinet completely insulated with high density polyurethane for low environmental impact.

### Construction

- Stainless steel interior and exterior, durable and easy to clean for daily commercial use.
- Self-closing door with 90-degree stay-open feature.
- Heavy duty casters.
- Pre-wired heavy duty power cord.
- · Heavy duty door hinges.
- Magnetic gasket removable without tools for easy cleaning.

# **Sustainability**

- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- CFC and HCFC free (ecological refrigerant type: R600a).


# **Optional Accessories**


- 1 ADJUSTABLE FOOT
- PNC 206445 🖵
- Drawer Kit for 60" Mega Top & Undercounter
- PNC 880617 📮

APPROVAL:



## Refrigeration Equipment 2-Door Under Counter Refrigerator 61" Long





EI = Electrical connection

#### **Electric**

Supply voltage:

**738291 (KCHUC60R)** 115 V/1 ph/60 Hz

Electrical power, max: 0.31 kW

Plug type: USA NEMA 5-15P

### **Capacity:**

Gross capacity: 15.5 cu.feet

#### **Key Information:**

Door hinges:1 Left+1 RightExternal dimensions, Width:61 1/4" (1555 mm)External dimensions, Depth:29 15/16" (760 mm)External dimensions, Height:35 1/2" (902 mm)

Number and type of doors: 2 Full

Internal Dimensions (depth):22 13/16" / (580 mm)Internal Dimensions (height):23 1/2" / (597 mm)Internal Dimensions (width):22 1/4" / (565 mm)Shipping height:38 3/16" (970 mm)Shipping weight:291 lbs (132 kg)Shipping volume:43.7 ft³ (1.24 m³)

Number and type of grids

(included): 2 - Vinyl-Coated Steel

Type of external material:Stainless SteelType of internal material:PolystyreneWarranty:3 / 5 years

ENERGY STAR;ETL C&US;ETL

Approvals SANITATION

#### **Refrigeration Data**

Compressor power:1/8 hpOperating temperature min.:32 °FOperating temperature max.:41 °FCondenser type:Fin & tubeDefrost type:Auto Defrost

#### **Sustainability**

Current consumption:3 AmpsRefrigerant type:R600aGWP Index:3Refrigerant weight:80 g











Refrigeration Equipment 2-Door Under Counter Refrigerator 61" Long