

Refrigeration Equipment 2-Door Under Counter Refrigerator 61" Long

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



738291 (KCHUC60R)

2-Door Under Counter Refrigerator 61" Long

Short Form Specification

Item No.

2-door refrigerator counter top, 35.5 inches tall, with exterior back panel, exterior bottom panel, and exterior top panel in galvanized steel, exterior side panel in 430 stainless steel; interior back, top and bottom panels in 304 stainless steel. Fin & tube condenser to improve the performances in high temperature = environments. Automatic Defrost Cooling System and temperature control. Vinyl heavy duty adjustable, easy to handle and clean shelves. External temperature display.

R600a gas in refrigeration circuit. ETL Safety and Sanitation certified.

3/5 Years warranty.

Main Features

- External temperature display.
- Removable gasket for easy cleaning operations.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.
- Heavy duty Vinyl coated steel shelves.
- Cabinet completely insulated with high density polyurethane for low environmental impact.
- · Adjustable shelves for flexible storage

Construction

- Stainless steel interior and exterior, durable and easy to clean for daily commercial use.
- Self-closing door with 90-degree stay-open feature.
- · Heavy duty casters.
- Pre-wired heavy duty power cord.
- Heavy duty door hinges.
- Magnetic gasket removable without tools for easy cleaning.

Sustainability

- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- CFC and HCFC free (ecological refrigerant type: R600a).


Optional Accessories


- 1 ADJUSTABLE FOOT
- PNC 206445 🖵
- Drawer Kit for 60" Mega Top & Undercounter
- PNC 880617 □

APPROVAL:



Refrigeration Equipment 2-Door Under Counter Refrigerator 61" Long





El = Electrical connection

Electric

Supply voltage: 115 V/1 ph/60 Hz **Electrical power, max:** 0.31 kW

Plug type: USA NEMA 5-15P

Capacity:

Gross capacity: 15.5 cu.feet

Key Information:

Number and type of grids

(included): 2 - Vinyl-Coated Steel

Warranty: 3 / 5 years

Door hinges: 1 Left+1 Right

External dimensions, Width: 61 1/4" (1555 mm)

External dimensions, Depth: 29 15/16" (760 mm)

External dimensions, Height: 35 1/2" (902 mm)

Number and type of doors: 2 Full

Internal Dimensions (depth): 22 13/16" / (580 mm) Internal Dimensions (height): 23 1/2" / (597 mm) Internal Dimensions (width): 22 1/4" / (565 mm) Shipping height: 38 3/16" (970 mm) Shipping weight: 291 lbs (132 kg) Shipping volume: 43.7 ft³ (1.24 m³) Type of external material: Stainless Steel Type of internal material: Polystyrene

ENERGY STAR;ETL C&US;ETL

SANITATION

Refrigeration Data

Approvals

Condenser type: Fin & tube
Operating temperature min.: 32 °F
Compressor power: 1/8 hp
Operating temperature max.: 41 °F

Patreet type:

Defrost type: Auto Defrost

Sustainability

Current consumption:3 AmpsRefrigerant type:R600aGWP Index:3Refrigerant weight:80 g











Refrigeration Equipment 2-Door Under Counter Refrigerator 61" Long