

Refrigerated bases 4-Drawer Chef Base Refrigerator 74" Long

738312 (KCHCB72R)	4-Drawer Chef Base Refrigerator 74" Long	S			
Short Form Specification					

<u>Item No.</u>

4-drawer Refrigerated base with exterior back panel, exterior side panels, and exterior control panel in 430 stainless steel, exterior bottom panel in galvanized steel; interior back panel in 430 stainless steel, interior bottom and interior side panels in 304 stainless steel. Top in 304 stainless steel. Electronic temperature control.

R290 gas in the refrigeration circuit.ETL Safety and Sanitation certified.3/5 Years warranty

ITEM #	 	 	
MODEL #			
NAME #			
SIS #			
AIA #			

Main Features

- External temperature display.
- Cabinet completely insulated with high density polyurethane for low environmental impact.
- Reccomended maximum temperature on worktop surface is 572°F.
- Insulation of the top guaranteed thanks to the Integrated ceramic fiber heat shield.
- Removable gasket for easy cleaning operations.
- Fin & Tube Condenser improves performance in high temperature environments.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.

Construction

- Pre-wired heavy duty power cord.
- Stainless steel interior and exterior, durable and easy to clean for daily commercial use.
- Heavy duty casters.
- Magnetic gasket removable without tools for easy cleaning.
- Heavy duty drawer runners.

Sustainability

- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) - CFC and HCFC free.

Optional Accessories

• 1 ADJUSTABLE FOOT

PNC 206445 🗅

APPROVAL:

Part of



Refrigerated bases 4-Drawer Chef Base Refrigerator 74" Long

Electric

Front

	74"-1880mm	
	72"-1829mm	
_	< <u>25.6"-650mm</u> >	13"-330mm
m v		
26"-660mm 200mm		
26"-66		
7.9	_₩	₩V.
		Side
	57.9"-1470mm	Siue
	31.9"-810mm 28.7"-730mm	->
	<u> </u>	
		-1
	20 	in l
	T T	
EI =	= Electrical connection	
		Тор
<	74"-1880mm	>
li		i
1		
Ĺ		¦

Supply voltage: 115 V/1 ph/60 Hz **Electrical power, max:** 0.22 kW Plug type: USA NEMA 5-15P **Key Information:** Warranty 3/5 External dimensions, Width: 74 1/32" (1880 mm) External dimensions, Depth: 31 7/8" (810 mm) **External dimensions, Height:** 26 " (660 mm) Internal Dimensions (depth): 26 13/16" / (680.72 mm) Internal Dimensions (height): 13 11/16" / (347.98 mm) Internal Dimensions (width): 51 13/16" / (1315.72 mm) Net weight: 287 lbs (130 kg) Shipping width: 32 7/8" (835 mm) Shipping depth: 75 3/16" (1910 mm) Shipping height: 28 3/8" (720 mm) Shipping weight: 359 lbs (163 kg) Shipping volume: 40.55 ft³ (1.15 m³) **Approvals** ETL C&US;ETL SANITATION N° of drawers: 4 Gross capacity: 355 lt

Refrigeration Data

Condenser type:	Fin & tube
Operating temperature min.:	32 °F
Compressor power:	1/5 hp
Operating temperature max.:	41 °F
Defrost type:	Auto Defrost

Sustainability

Current consumption: Refrigerant type: Refrigerant weight:

2.1 Amps R290 80 g



Refrigerated bases 4-Drawer Chef Base Refrigerator 74" Long

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

Kelvinator Commercial is a pending or registered trademark of Electrolux Consumer Products, Inc., and is used under a license from Electrolux Consumer Products, Inc.