

Refrigeration Equipment 1-Door Full Height 220V Freezer 27" Long

ITEM # _____
MODEL # _____
NAME # _____
SIS # _____
AIA # _____



738341
(KCHRI27R1DFE-220)

1-Door Full Height 220V
Freezer 27" Long

Short Form Specification

Item No.

1 full door freezer, 220V, with exterior top, back, and bottom panels in galvanized steel, exterior side panels in 430 stainless steel; interior back, side, top and bottom panels in 304 stainless steel. Control with cabinet temperature display. Self-closing and on-site reversible door feature with lock and key. R290 gas in the refrigeration circuit.

Main Features

- External temperature display.
- Removable gasket for easy cleaning operations.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.
- Heavy duty Vinyl coated steel shelves.
- Cabinet completely insulated with high density polyurethane for low environmental impact.
- Bottom mounted cooling unit slides out for easy access and cleaning.

Construction

- Lockable door.
- Stainless steel interior and exterior, durable and easy to clean for daily commercial use.
- Self-closing door with 90-degree stay-open feature.
- Heavy duty casters.
- Heavy duty door hinges.
- Magnetic gasket removable without tools for easy cleaning.


Sustainability

- Interior LED light to save energy and for best internal visibility.
- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) - CFC and HCFC free.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.


Optional Accessories

- 1 ADJUSTABLE FOOT PNC 206445 ☐
- Shelf for 27" Reach-In (Solid Door) PNC 880590 ☐
- Shelf clips (4-pack) PNC 880611 ☐

APPROVAL: _____




Front



Side

EI = Electrical connection



Top

Electric

Supply voltage:	220 V/1 ph/50 Hz
Electrical power, max:	950 kW

Capacity:

Number and type of grids (included):	3 - ;618x548
Gross capacity:	21.1 cu.feet

Key Information:

Door hinges:	Right Side
Capacity:	21.0621 cu.ft.
External dimensions, Width:	26 3/4" (680 mm)
External dimensions, Depth:	32 11/16" (830 mm)
External dimensions, Height:	83 " (2108 mm)
Number and type of doors:	1 ; Full
Internal Dimensions (depth):	27 1/2" / (698.5 mm)
Internal Dimensions (height):	50 3/16" / (1275.08 mm)
Internal Dimensions (width):	22 3/16" / (563.88 mm)
Shipping height:	84 5/8" (2150 mm)
Shipping weight:	328 lbs (149 kg)
Shipping volume:	49.91 ft³ (1.41 m³)
Type of external material:	Stainless Steel
Type of internal material:	304 AISI
Approvals	CE

Refrigeration Data

Condenser type:	Fin & tube
Operating temperature min.:	-10.01 °F
Compressor power:	4/5 hp
Operating temperature max.:	0 °F
Defrost type:	Auto Defrost

Sustainability

Current consumption:	4.9 Amps
Refrigerant type:	R290
Refrigerant weight:	90 g

