

Refrigeration Equipment 4-Tub Ice Cream Dipping Cabinet 33" Long

ITEM # _____
MODEL # _____
NAME # _____
SIS # _____
AIA # _____



738371 (KCICDC4FH)

4-Tub Ice Cream Dipping
Cabinet 33" Long

Short Form Specification

Item No. _____

Front of the house display ice cream or gelato dipping cabinet. Exterior & interior panels stainless steel painted white, bottom panel is galvanized steel, top panel is galvanized material painted white to match. Fin & tube condenser to improve the performances in high-temperature environments. Automatic Defrost Cooling System and temperature control. Includes (1) NSF® certified temperature gauge, and (4) barrel ice cream tub frames; (4) gelato pan is an available option. Front is radius white plastic, lit from behind, for customer supplied signage if desired. Additional freezer storage on operator side.

Ropack tub bracket insert included after serial number 004332000182

Main Features

- Fan cooled condenser to cope with heavy duty conditions
- Included as standard 1 NSF® certified temperature gauge and 4-barrel ice cream tub frame.
- Bottom drain with plug for easy interior cleaning and defrost water discharge
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.

Construction

- Tempered glass viewing panels & sliding lids
- Plexiglass sliding shields.
- Exterior and Interior finish in white
- Locking lids and key protect the contents of the unit.
- Heavy-duty, locking casters keeps the unit in place but allow position adjusting.



Sustainability

- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) - CFC and HCFC free.
- Low energy consumption thanks to high efficiency components, insulation and optimized airflow.

Optional Accessories

- Combined 5L Pan Support Metal PNC 882012 ☐
Frame & 5L Pan Support Acrylic
Frame for 4 Tub Ice Cream Dipping
Cabinet

APPROVAL: _____



El = Electrical connection

Electric

Supply voltage:	115 V/1 ph/60 Hz
Electrical power, max:	0.2 kW
Plug type:	USA NEMA 5-15P

Capacity:

Gross capacity:	8.3 cu.feet
-----------------	-------------

Key Information:

Warranty:	3 / 5 years
External dimensions, Width:	32 15/16" (836 mm)
External dimensions, Depth:	33 " (838 mm)
External dimensions, Height:	50 " (1270 mm)
Internal Dimensions (depth):	23 5/8" / (600 mm)
Internal Dimensions (height):	25 13/16" / (656 mm)
Internal Dimensions (width):	21 5/8" / (550 mm)
Shipping height:	50 9/16" (1285 mm)
Shipping weight:	238 lbs (108 kg)
Shipping volume:	44.01 ft ³ (1.25 m ³)
Type of external material:	Prepainted white
Type of internal material:	White Prepainted Steel
Approvals	ETL C&US;ETL SANITATION

Refrigeration Data

Condenser type:	Fin & tube
Operating temperature min.:	-18.4 °F
Compressor power:	1/5 hp
Operating temperature max.:	6.8 °F
Defrost type:	Automatic

Sustainability

Current consumption:	1.3 Amps
Refrigerant type:	R290
GWP Index:	3
Refrigerant weight:	68 g