

### COMMERCIAL

# Chest Freezer 7 ft.<sup>3</sup> Novelty Freezer, 1 Basket

ITEM #		
MODEL #		
NAME #		
SIS #		
ΛΙΛ #		



738090 (KCNF073WS)

Sliding Glass Lid Novelty Freezer 38" Long

# **Short Form Specification**

#### Item No.

Glass lids top chest freezer with internal structure in painted steel and external structure in textured painted steel. Fan cooler condenser and 1/6 HP compressor. Freezer baskets and internal digital control with cabinet temperature display.

Locking lids and key to protect the contents in the unit. Equipped with NEMA 5-15P plug.

Basket and NSF®-Certified Temperature Gauge.

### **Main Features**

- Static Condenser
- 1/6 HP Compressor
- · Mechanical Control
- Internal Temperature Display
- Freezer Basket
- . Locking Lids & Key Protect the contents of the unit
- Exterior Finish: Textured Painted Steel
- · Interior Finish: Painted Steel
- Basket Durable and reliable for safety in food storage (1 basket included).
- NSF®-Certified Temperature Gauge Durable and reliable for safety in food storage.
- Heavy-Duty, Locking Casters Keeps unit in place but allows position adjusting.


# **Optional Accessories**


• - NOT TRANSLATED - PNC 882003 □

**APPROVAL:** 



# Chest Freezer 7 ft.<sup>3</sup> Novelty Freezer, 1 Basket





EI = Electrical connection

### **Electric**

Supply voltage:

**738090 (KCNF073WS)** 115 V/1 ph/60 Hz

Electrical power, max: 0.3 kW

Plug type: USA NEMA 5-15P

## **Capacity:**

Capacity: 7 ft.<sup>3</sup>

## **Key Information:**

External dimensions, Width: 37 13/16" (960 mm) External dimensions, Depth: 20 11/16" (525 mm) **External dimensions, Height:** 33 1/16" (840 mm) Internal dimensions, Width: 32 1/16 " (814 mm) Internal dimensions, Height: 27 1/4" (692 mm) Internal dimensions, Depth: 14 7/8" (378mm) Net weight: 88 lbs (40 kg) Shipping width: 22 13/16" (580 mm) Shipping height: 34 13/16" (885 mm) Shipping weight: 160 lbs (72.72 kg) Shipping volume: 18.22 ft3 (0.52 m3)

### **Refrigeration Data**

Refrigerant type: R600a
Operating temperature min.: -10 °F
Operating temperature max.: 10 °F







