

Chest Freezer Solid Top Chest Freezer 59.5 " Long

738231 (KCCF170WH)	Solid Top Chest Freezer 59.5 " Long

Short Form Specification

<u>ltem No.</u>

Solid top chest freezer, 59.5 inches long, with foamed lid and soft closing mechanism to ensure gentle lid closure. Internal and external structure in white painted steel. Basket, vertical basket divider, NSF thermometer and lock included as standard. Defrost water drain with plug for easy cleaning. R290 refrigerant gas for the lowest environmental impact (GWP=3).

The temperature range is -15° to 10°F.

ETL safety and sanitation listed for US and Canada. Equipped with NEMA 5-15P plug.

ITEM #			
MODEL #			
NAME #			
SIS #			
AIA #			

Main Features

- Temperature range of -15 to +10 F°
- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) CFC and HCFC free.
- Low energy consumption
- Mechanical control panel with adjustable temperature
- Included as standard 1 NSF® certified temperature gauge and 1 basket (including one vertical divider) durable and reliable for safety in food storage
- Removable rubber bumper guards
- Bottom drain with plug for easy interior cleaning and defrost water discharge

Construction

- Foamed lid for best insulation and product robustness
- Soft closing lid mechanism
- Static condenser
- Exterior and Interior finish in white painted steel
- Locking lid and key protect the contents of the unit
- Mounted on heavy-duty casters, two locking to keep unit in place but allows position adjusting.

Sustainability

- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) CFC and HCFC free.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.

Optional Accessories

 Basket for Solid Top Chest Freezer PNC 882000 22.63x8.15x7.52 in. (575x207x191 mm)

APPROVAL:



Kelvinator Commercial www.kelvinatorcommercial.com



EI =

6"

Chest Freezer Solid Top Chest Freezer 59.5 Long

Supply voltage: Electrical power, max: Plug type: Capacity: Capacity: Capacity: Control Warranty External dimensions, M External dimensions, M External dimensions, M External dimensions, M External dimensions, M Internal Dimensions (d Internal Dimensions (d) Internal Di		Front Electric
Gross capacity: Key Information Freezer baskets (Numb Control Warranty External dimensions, U External dimensions, U External dimensions (d Internal Dimensions (d Internal Dimensions (d) Internal Dimensions (d)	1510.4 mm	Electrical power, max:
Key Information Freezer baskets (Numb Control Warranty) External dimensions, M External dimensions, M External dimensions, M I = Electrical connection **********************************		Capacity:
Freezer baskets (Numb Control Waranty External dimensions, D External dimensions, C I = Electrical connection 0 29 3/10* 1 29 3/10* 1 58 def 0 10 1 Electrical connection 0 1/206mm 1/206mm 1/206mm <td< th=""><th></th><th></th></td<>		
Control Warranty External dimensions, M External dimensions, M External dimensions (d Internal Dimensions (d Inter	1 2 5mm	
	$\frac{29 \ 3/10^{\prime}}{743 \ mm}$ $\frac{29 \ 3/10^{\prime}}{743 \ mm}$ $\frac{743 \ mm}{1206 \ mm}$ $\frac{1206 \ mm}{231.5 \ mm}$	SideControl Warranty External dimensions, D External dimensions, D External dimensions, D External dimensions, D External dimensions, D External dimensions, D External dimensions (d Internal Dimensions (d Internal Dimensions (d Internal Dimensions (d Internal Dimensions (d) Shipping weight: Shipping weight: Shipping weight: Shipping weight: Shipping volume:TopRefrigeration Condenser type: Temperature display lo Operating temperature Compressor power: Operating temperatureTopSustainability GWP Index: Refrigerant weight: Shipping reget

0.2 kW USA NEMA 1-15P 17.7 cu.feet ion: nber/Type): 1 / Wire Mechanical 1/5 Years Width: 59 7/16" (1510 mm) Depth: 29 5/16" (744.22 mm) Height: 36 1/2" (927 mm) (depth): 21 5/8" / (550 mm) (width): 53 3/4" / (1366 mm) 170 lbs (77 kg) 30 1/2" (775 mm) 42 1/64" (1067 mm) 205 lbs (93 kg) 46.22 ft3 (1.31 m3) ENERGY STAR; ETL C&US; ETL SANITATION

115 V/1 ph/60 Hz

Data

Condenser type:	Static
Temperature display location:	Internal
Operating temperature min.:	-20.2 °F
Compressor power:	1/5 hp
Operating temperature max.:	10.4 °F

Current consumption:	1.9 Amps
Refrigerant type:	R290
GWP Index:	3
Refrigerant weight:	119 g



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

Kelvinator Commercial is a pending or registered trademark of Electrolux Consumer Products, Inc., and is used under a license from Electrolux Consumer Products, Inc.

("])

15A 125V NEMA 5-15P

Intertek

Intertek