

COMMERCIAL

Chest Freezer Novelty Freezer, 18 cu.ft , 1 Basket



for best preservation performance even in heavy-duty conditions. Basket, vertical basket divider, NSF thermometer and lock included as standard. Defrost water drain with plug for easy cleaning. R290 refrigerant gas for the lowest environmental impact (GWP=3). The temperature range is -10° to 10°F. ETL safety and sanitation listed for US and Canada. Equipped with NEMA 5-15P plug.

TEM #	_
MODEL #	
NAME #	
SIS #	_
AIA #	

Main Features

- Temperature range of -10 to +10 F°
- Fan cooled condenser to cope with heavy duty conditions
- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) CFC and HCFC free.
- Included as standard 1 NSF® certified temperature gauge and 1 basket (including one vertical divider) durable and reliable for safety in food storage
- Removable rubber bumper guards
- Bottom drain with plug for easy interior cleaning and defrost water discharge
- Mechanical control panel with adjustable temperature
- Low energy consumption

Construction

- Tempered glass sliding lids
- Exterior and Interior finish in white painted Steel
- · Locking lids and key protect the contents of the unit
- Mounted on heavy-duty casters, two locking to keep unit in place but allows position adjusting.

Optional Accessories

- - NOT TRANSLATED -
- PNC 882001 🗅

APPROVAL:





V

70 9/10" 1800 mm

27 3/10" 694 mm

Π

EI = Electrical connection

Chest Freezer Novelty Freezer, 18 cu.ft , 1 Basket

Electric

<u>1"</u> 24 mm

218

35 2/5" 900 mm


3/10″ 6 m

16 3/5" 422 mm


Eront	Electric	
	Supply voltage: 738234 (KCNF170WH) Electrical power, max: Plug type:	115 V/1 ph/60 Hz 0.3 kW USA NEMA 5-15P
31 7/10" 804 mm	Capacity:	
	Capacity:	17.7 ft. ³
	Key Information:	
Side	External dimensions, Width: External dimensions, Depth: External dimensions, Height: Condenser type: Automatic Defrost Cooling System: Compressor Horsepower: Freezer baskets (Number/Type): Control Warranty Net weight: Shipping width: Shipping height: Shipping weight:	70 7/8" (1800.86 mm) 27 5/16" (693.42 mm) 34 13/16" (883.92 mm) Static No 1/5 1 / Wire Mechanical 1/5 Years 209 lbs (95 kg) 30 3/16" (767 mm) 37 13/16" (960 mm) 209 lbs (95 kg)
,,	Shipping volume: Refrigeration Data	48.67 ft³ (1.38 m³)
	Temperature display location:	Internal

Temperature display location: Temperature range: **Refrigerant type:**

Internal -15 to 10 °F R290



⊕ ⊕ Intertek Intertek Intertek



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.