



COMMERCIAL

Refrigeration Equipment 2-Door Pizza Prep Table 71 " Long 9-1/3 Pan


ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



738253 (KCHPT72.9)

2-Door Pizza Prep Table 71
" Long 9-1/3 Pan

Short Form Specification

Item No. _____

2-door pizza refrigerated preparation table. Exterior back panel in aluminium, exterior bottom panel in galvanized steel, exterior side and top panel in 430 stainless steel; interior back, side panels and bottom panel in 304 stainless steel, worktop in 430 stainless steel.

Built-in refrigeration unit and an insulated lid to maintain food freshness. Fin & Tube Condenser improves performance in high-temperature environments. Automatic Defrost Cooling System to provide worry-free performances.

Full-depth cutting board of 79x70.79x19.53 in.

Control panel, Vinyl-Coated Steel adjustable shelves, removable door gaskets and self-closing doors with 90-degree stay-open feature.

Temperature range: +33/+41°F.

R290 gas in the refrigeration circuit.

ETL Safety and Sanitation certifications.

3/5 Years warranty.

Main Features

- External temperature display.
- Removable gasket for easy cleaning operations.
- Fin & Tube Condenser improves performance in high temperature environments.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.
- Full Depth cutting board.
- Cabinet completely insulated with high density polyurethane for low environmental impact.
- Heavy duty Vinyl coated steel shelves.

Construction

- Heavy duty casters.
- Insulated lid maintains food freshness.
- Holds 9 1/3 pans.
- Pre-wired heavy duty power cord.
- Heavy duty door hinges.
- Magnetic gasket removable without tools for easy cleaning.


Sustainability

- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) - CFC and HCFC free.

Optional Accessories

- Shelf for 72" Pizza Counter PNC 880602
- Shelf clips (4-pack) PNC 880611

APPROVAL: _____



Electric

Supply voltage:	738253 (KCHPT72.9)	115 V/1 ph/60 Hz
Electrical power, max:		0.78 kW
Plug type:		NEMA 5-15

Capacity:

Gross capacity:	22 cu.feet
-----------------	------------

Key Information:

Door hinges:	1 Left+1 Right
Capacity:	22 cu.ft.
External dimensions, Width:	70 13/16" (1798 mm)
External dimensions, Depth:	32 1/4" (820 mm)
External dimensions, Height:	41 5/16" (1050 mm)
Number and type of doors:	2 Full
Internal Dimensions (depth):	22 13/16"
Internal Dimensions (height):	26 3/16"
Internal Dimensions (width):	48 7/16"
Net Weight:	408 lbs
Shipping height:	44 1/2" (1130 mm)
Shipping weight:	397 lbs (180 kg)
Shipping volume:	63.65 ft ³ (1.8 m ³)
Type of grids (included):	Vinyl-Coated steel
Type of external material:	Stainless Steel
Type of internal material:	304 AISI
Warranty:	3 / 5 years

Refrigeration Data

Compressor power:	1/3 hp
Operating temperature min.:	32 °F
Operating temperature max.:	41 °F
Condenser type:	Fin & tube
Defrost type:	Auto Defrost

Sustainability

Current consumption:	7.5 Amps
Refrigerant type:	R290
Refrigerant weight:	105 g