

## **Refrigeration Equipment** 2-Door Refrigerator Under **Counter 48" Long**

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



738264 (KCHUC48R)

2-Door Refrigerator Under Counter 48" Long

## **Short Form Specification**

Item No.

2-door refrigerator counter top, 35.5 inches tall, with exterior back panel, exterior

bottom panel, and exterior top panel in galvanized steel, exterior side panel in 430 stainless steel; interior back, top and bottom panels in 304 stainless steel. Fin & tube condenser to improve the performances in high temperature environments. Automatic Defrost Cooling System and temperature control. Vinyl heavy duty adjustable, easy to handle and clean shelves. External temperature display. R600a gas in refrigeration circuit.

ETL Safety and Sanitation certified.

3/5 Years warranty.

### **Main Features**

- External temperature display.
- Removable gasket for easy cleaning operations.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.
- Heavy duty Vinyl coated steel shelves.
- Cabinet completely insulated with high density polyurethane for low environmental impact.

#### Construction

- Self-closing door with 90-degree stay-open feature.
- Heavy duty casters.
- Pre-wired heavy duty power cord.
- Heavy duty door hinges.
- Magnetic gasket removable without tools for easy cleaning.

## Sustainability

- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- CFC and HCFC free (ecological refrigerant type: R600a).


# **Optional Accessories**


- 1 ADJUSTABLE FOOT
- PNC 206445 🔲
- Drawer Kit for 48" Mega Top, Salad PNC 880616  $\Box$ Top, Undercounter and L/R section of 70" Salad & Mega Top and 72" Undercounter

APPROVAL:



## Refrigeration Equipment 2-Door Refrigerator Under Counter 48" Long





**Electric** 

Supply voltage:

**738264 (KCHUC48R)** 115 V/1 ph/60 Hz

Electrical power, max: 0.31 kW

Plug type: USA NEMA 5-15P

Capacity:

Gross capacity: 12 cu.feet

### **Key Information:**

Door hinges:1 Left+1 RightExternal dimensions, Width:48 1/4" (1225 mm)External dimensions, Depth:29 15/16" (760 mm)External dimensions, Height:35 1/2" (902 mm)

Number and type of doors: 2 Full

Internal Dimensions (depth): 22 13/16" / (580 mm)
Internal Dimensions (height): 23 1/2" / (597 mm)
Internal Dimensions (width): 42 1/2" / (1080 mm)
Shipping height: 38 3/16" (970 mm)
Shipping weight: 238 lbs (108 kg)
Shipping volume: 34.66 ft³ (0.98 m³)

Number and type of grids

(included): 2 - Vinyl-Coated Steel

Type of external material: Stainless Steel
Type of internal material: Polystyrene
Warranty: 3 / 5 years

ENERGY STAR;ETL C&US;ETL

Approvals SANITATION

### **Refrigeration Data**

Current absorbed: 3 Amps
Compressor power: 1/8 hp
Operating temperature min.: 32 °F
Operating temperature max.: 41 °F
Condenser type: Fin & tube
Defrost type: Auto Defrost

### **Sustainability**

Refrigerant type: R600a GWP Index: 3 Refrigerant weight: 75 g

energy STAR

Electrical connection









Refrigeration Equipment 2-Door Refrigerator Under Counter 48" Long