

**Refrigeration Equipment
Undercounter Refrigerator, 27" with
1 Door with Worktop - Stainless
Steel (R600a)**

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



738299 (KCHUCWT27R)

1-door undercounter refrigerator with worktop, 27", R600a refrigerant gas, 33/+41 °F, stainless steel - Energy star

Short Form Specification

Item No. _____

1-door refrigerated counter top with exterior back panel in aluminium, exterior bottom panel in galvanized steel, exterior side and top panel in 430 stainless steel; interior back, top and bottom panels in 304 stainless steel.

Fin & tube condenser to improve the performances in high temperature environments. Automatic Defrost Cooling System and temperature control. Vinyl heavy duty adjustable, easy to handle and clean shelves. External temperature display.

R600a gas in refrigeration circuit.
ETL Safety and Sanitation certified.
3/5 Years warranty.

Main Features

- External temperature display.
- Removable gasket for easy cleaning operations.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.
- Heavy duty Vinyl coated steel shelves.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- Cabinet completely insulated with high density polyurethane for low environmental impact.


Construction

- Self-closing door with 90-degree stay-open feature.
- Heavy duty casters.
- CFC and HCFC free (ecological refrigerant type: R600a).
- Pre-wired heavy duty power cord.
- Heavy duty door hinges.
- Magnetic gasket removable without tools for easy cleaning.

Optional Accessories

- shelf for 27" undercounter PNC 880599
- shelf clips PNC 880611
- drawers kit for 27" undercounter PNC 880614

APPROVAL: _____



Electric

Supply voltage:	738299 (KCHUCWT27R)	115 V/1 ph/60 Hz
Electrical power, max:		0.2 kW
Current consumption:		1.5 Amps
Plug type:		USA NEMA 5-15P

Key Information:

Door hinges:	Right Side
Capacity (Cu. Ft.)	27
External dimensions, Width:	27 3/4" (705 mm)
External dimensions, Depth:	29 15/16" (760 mm)
External dimensions, Height:	39 7/16" (1002 mm)
Number and type of doors:	1 Full
Internal Dimensions (depth):	22 13/16"
Internal Dimensions (height):	23 1/2"
Internal Dimensions (width):	22 1/4"
Shipping height:	42 1/8" (1070 mm)
Shipping weight:	190 lbs (86 kg)
Shipping volume:	22.52 ft ³ (0.64 m ³)
Number and type of grids (included):	1 - Vinyl-Coated Steel
Type of external material:	Stainless Steel
Type of internal material:	Polystyrene
Warranty:	3 / 5 years

Refrigeration Data

Compressor Horsepower:	1/6
Refrigerant type:	R600a
Refrigerant weight:	70 g
Operating temperature min.:	32 °F
Operating temperature max.:	41 °F
Condenser type:	Fin & tube
Defrost type:	Auto Defrost