

COMMERCIAL

Refrigeration Equipment 3-Door Work Top Refrigerator 72" Long

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



738302 (KCHUCWT72R)

3-Door Work Top Refrigerator 72" Long

Short Form Specification

Item No.

3-door refrigerated counter top with exterior back panel in aluminium, exterior bottom panel in galvanized steel, exterior side and top panel in 430 stainless steel; interior back, top and bottom panels in 304 stainless steel.

Fin & tube condenser to improve the performances in high temperature environments. Automatic Defrost Cooling System and temperature control. Vinyl heavy duty adjustable, easy to handle and clean shelves. External temperature display.

R600a gas in refrigeration circuit. ETL Safety and Sanitation certified.

3/5 Years warranty.

Main Features

- External temperature display.
- · Removable gasket for easy cleaning operations.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.
- · Heavy duty Vinyl coated steel shelves.
- Cabinet completely insulated with high density polyurethane for low environmental impact.

Construction

- Self-closing door with 90-degree stay-open feature.
- · Heavy duty casters.
- Pre-wired heavy duty power cord.
- · Heavy duty door hinges.
- Magnetic gasket removable without tools for easy cleaning.

Sustainability

- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- CFC and HCFC free (ecological refrigerant type: R600a).


Optional Accessories


shelf for 48" and 72" (left/right) mega top, salad and undercounter
 middle shelf for 72" mega top, salad and oundercounter
 shelf clips
 PNC 880598 and PNC 880611

APPROVAL:



Refrigeration Equipment 3-Door Work Top Refrigerator 72" Long





EI = Electrical connection

Electric

Supply voltage:

738302 (KCHUCWT72R) 115 V/1 ph/60 Hz

Electrical power, max: 0.4 kW

Plug type: USA NEMA 5-15P

Key Information:

Door hinges:1 Left+2 RightExternal dimensions, Width:71 3/4" (1822 mm)External dimensions, Depth:29 15/16" (760 mm)External dimensions, Height:39 7/16" (1002 mm)

Number and type of doors: 3 Full
Internal Dimensions (depth): 24 13/16"
Internal Dimensions (height): 24 7/16"
Internal Dimensions (width): 66 15/16"

Shipping height:42 1/8" (1070 mm)Shipping weight:357 lbs (162 kg)Shipping volume:56.28 ft³ (1.59 m³)

Number and type of grids

(included): 3 - Vinyl-Coated Steel

Type of external material: Stainless Steel
Type of internal material: 304 AISI
Warranty: 3 / 5 years

Refrigeration Data

Compressor Horsepower: 1/6

Operating temperature min.: ISO 9001 °F
Operating temperature max.: 41 °F
Condenser type: Fin & tube
Defrost type: Auto Defrost

Product Information (EU Regulation 2015/1094)

Capacity (Cu.Ft.) 72

Sustainability

Current consumption:3.5 AmpsRefrigerant type:R290Refrigerant weight:125 g









