



COMMERCIAL

Refrigeration Equipment 4 Half Glass Door Refrigerator 49 CU.FT S/S (R290)

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



738316 (KCHRI54R4HGDR) 4-Half Glass Door Full Height Refrigerator 54" Long

Short Form Specification

Item No. _____

4-half glass door refrigerator with exterior back and bottom panels in galvanized steel, exterior side and top panels in 430 stainless steel; interior back, side, top and bottom panels in 304 stainless steel. Control with cabinet temperature display. Self-closing and on-site reversible door feature lock and key. R290 gas in the refrigeration circuit. ETL Safety and Sanitation certifications. 3/5 Years warranty.


Main Features

- External digital temperature display.
- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- Removable gasket for easy cleaning operations.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- Cabinet completely insulated with high density polyurethane for low environmental impact.
- Back bottom mounted cooling unit guarantee an easy access and cleaning.
- Heavy duty Vinyl coated steel shelves.
- Interior LED light to save energy and for best internal visibility.

Construction

- Stainless steel interior and exterior, durable and easy to clean for daily commercial use.
- Lockable door.
- Heavy duty casters.
- Magnetic gasket removable without tools for easy cleaning.
- Pre-wired heavy duty power cord.
- Heavy duty door hinges.

APPROVAL: _____



Electric

Supply voltage:	738316 (KCHRI54R4HGDR)	120 V/1 ph/60 Hz
Electrical power, max:		0.5 kW
Plug type:		NEMA 5-15

Key Information:

Door hinges:	2 Left+2 Right
Capacity (Cu. Ft.)	49
External dimensions, Width:	55 5/16" (1405 mm)
External dimensions, Depth:	34 1/16" (865 mm)
External dimensions, Height:	84 5/8" (2150 mm)
Number and type of doors:	4x1/2 ;Glass
Internal Dimensions (depth):	27 9/16"
Internal Dimensions (height):	59 7/16"
Internal Dimensions (width):	49 3/8"
Shipping height:	87 1/64" (2210 mm)
Shipping weight:	628 lbs (285 kg)
Shipping volume:	98.76 ft ³ (2.8 m ³)
Number and type of grids (included):	3 - Vinyl-Coated steel
Type of External Material:	430 ASI
Type of internal material:	304 AISI
Warranty:	3 / 5 years

Refrigeration Data

Compressor Horsepower:	1/6
Operating temperature min.:	34.5 °F
Operating temperature max.:	38.8 °F
Condenser Type:	Fin & Tube
Defrost type:	Automatic

Sustainability

Current consumption:	4.5 Amps
Refrigerant type:	R290