# FROSTY, 1 BOWL, MECHANICAL CONTROL





Ref: 560568 (FROSTY1NEW)

SLUSH MACHINE FROSTY 1 STD 230/50 BLACK - GAS R452A

### **General Features**

FROSTY is the ideal slushy machine for those who want large-sized equipment with high performance, but with a low investment budget.

FROSTY 1 is the equipment for the production and dispensing of slushie, sorbets and other frozen specialties, with n. 1 tank with a capacity of 12 litres.

The tank is illuminated with a LED lighting system, for a strong appeal to the consumer, and encouraging impulse purchases.

FROSTY has a double mixing system prevents ice accumulation, for optimum product consistency.

This slush machine has a manual control keypad, to turn on/off the lights and set the "production" mode and the "night" mode"

# FROSTY, 1 BOWL, MECHANICAL CONTROL

## **Specifications**

- Safety stop system.
- It is possible to customize the graphics on the front, on the lid and on the back (subject to negotiation).
- Equipped with a LED lighting system to enhance product visibility, for a strong attraction effect, and to stimulate impulse purchases.
- Lockable lid
- Perfect for dispensing granitas, sorbets and other frozen specialties.
- The mechanical control allows you to manually set the start the "production mode" and the "night mode" and turn on/off the LED-lights.

#### Construction

- Double mixing system to guarantee a perfect consistency of the dispensed product.
- Slushy machine, equipped with 1x12-litres tank



# FROSTY, 1 BOWL, MECHANICAL CONTROL

### **Electric**

**Supply voltage:** 220-240 V / 1 ph / 50 Hz

Electrical power max.:0.5 kWCurrent consumption:3.4 AmpsPlug type:CE-SCHUKO

### **Key Information:**

Number of bowls: 1 Bowl's capacity: 12 lt Control board: Mechanical Dimensions, Width: 209 mm Dimensions, Depth: 564 mm Dimensions, Height: 832 mm Net weight: 34 kg Cooling system: AIR

### **Refrigeration Data**

Refrigerant gas: R452A

## **Certifications**



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.





