

# I-PRO 1 BOWL, WITH MECHANICAL CONTROL



I-PRO 1 BOWL, WITH MECHANICAL CONTROL

**Ref: 561494  
(IPRO1M)**

SLUSH MACHINE I-PRO 1 M STD 230/50 WHITE - GAS R290

## General Features

I-PRO 1 MECHANICAL is a professional slush machine with n. 1 I-Tank insulated bowl with a capacity of 11 litres, and mechanical control.

Every detail has been studied to create a unique equipment thanks to the numerous patents and innovations available for this model.

This equipment has the I-Tank insulated tank as standard. The shape of the tank guarantees a natural mixing effect, for an optimal consistency of the product.

The look of this equipment is modern and eye-catching, thanks to the LED-light system that illuminates the product inside the tank.

The equipment can dispense slushies, milkshakes, cold drinks and frozen drinks.

I-PRO is an ideal slush machine for bars, amusement parks, fast food chains, kiosks, restaurants, water parks and much more.

SPM

# I-PRO 1 BOWL, WITH MECHANICAL CONTROL

## Specifications

- I-PRO is an ideal slush machine for bars, amusement parks, motorway restaurants, fast food chains, kiosks, restaurants, water parks and much more.
- It is possible to customize the graphics on the front, on the lid and on the back (subject to negotiation).
- Optionals available: autofill lid (pre-mix or post-mix) for the automatic filling of the tanks.
- The special shape of the tank, with a capacity of 11 litres of finished product and LED-lighted, allows a natural mixing effect which guarantees a perfect consistency of the product.
- The equipment can dispense: granitas, slushies, milkshakes and cold drinks and frozen cocktails.

## Construction

- The patented I-Tank insulated bowl reduces the impact of ambient temperature on the product, improving its cooling efficiency and guaranteeing energy and cost savings.
- Slushie machine equipped with 1x11-litres insulated tank
- The mechanical control allows you to manually set the “production mode” and the “night mode”.

# I-PRO 1 BOWL, WITH MECHANICAL CONTROL

## Electric

|                        |                          |
|------------------------|--------------------------|
| Supply voltage:        | 220-240 V / 1 ph / 50 Hz |
| Electrical power max.: | 0.54 kW                  |
| Current consumption:   | 2.8 Amps                 |
| Plug type:             | CE-SCHUKO                |

## Key Information:

|                     |                        |
|---------------------|------------------------|
| Number of bowls:    | 1                      |
| Bowl's capacity:    | ISO 9001; ISO 14001 lt |
| Control board:      | Mechanical             |
| Dimensions, Width:  | 200 mm                 |
| Dimensions, Depth:  | 580 mm                 |
| Dimensions, Height: | 870 mm                 |
| Net weight:         | 39 kg                  |
| Cooling system:     | AIR                    |

## Refrigeration Data

|                  |      |
|------------------|------|
| Refrigerant gas: | R290 |
|------------------|------|

## Certifications



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2024.10.18

# SPM

[www.spm.drink-systems.com](http://www.spm.drink-systems.com)  
[infospm@electroluxprofessional.com](mailto:infospm@electroluxprofessional.com)