CLASSIC PLUS 2 groups, Tall cup, Steamair



Ref602944 (UCLASSIC2HPSGUL)

Traditional espresso maker, 2 group, tall cup configuration, 10,1 liter boiler, 2 independent control boxes with 4 programmable dosing program, Steamglide, Steamair, programmable water, automatic cleaning cycle, stainless steel body

General Features

High profile two group espresso maker with large steam boiler for direct preparation into large to-go cups (cup clearance up to 7"). Elegant lines and reliable technologies appreciated by coffee professionals, the CLASSIC model is made more attractive by its quality/ price ratio. Designed for rugged commercial application, the CLASSIC is the perfect traditional espresso machine to ensure an excellent quality espresso result, consistency and high performance during rush period. Steamair auto foam and auto temperature control.

CLASSIC PLUS 2 groups, Tall cup, Steamair

Main Features

- Maestro brew group: directly to boiler group heads are mounted for shot temperature stability.
- Large cup warming capacity: integrated cup warmer on the top of the machines.
- 4 programmable volume keys per group + Semi-automatic key for each group for manual control.
- Automatic cleaning program.
- Heavy duty components and welded construction, a direct mounted boiler group head for thermal stability and reliable extraction, easy access to components for uncomplicated servicability, and unlimited steam.
- The tall cup configuration allows the barista to easily prepare large size drinks according to the larger cup clearance available.
- Programmable steam and hot water.
- Steamair milk auto-frother programmable outlet.
- Manual Steamglide lever.

Construction

• Built-in cup warmer.

UNIC

CLASSIC PLUS 2 groups, Tall cup, Steamair

Electric

Supply voltage: 602944 (UCLASSIC2HPSGUL) 220 V/1 ph/60 Hz Electrical power, max: 4.3 kW


Plug type:

Water:

Cold water temperature (min/max): 5 / 60 °C

Key Information:

External dimensions, Width:	25 1/4" (642 mm)
External dimensions, Depth:	22 7/16" (568 mm)
External dimensions, Height:	25 9/16" (650 mm)
External dimensions, Weight:	121 lbs (65 kg)
Net weight:	121 lbs (65 kg)
Shipping width:	(1100 mm)
Shipping depth:	(750 mm)
Shipping height:	(840 mm)
Shipping weight:	lbs (82 kg)
Shipping volume:	0.7 m ³



Certifications



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2024.07.04

Part of Professional Group

UNIC