

## TANGO ST SOLO 121, Steamair



### Ref602745 (SOLOST121SAUL)

Super automatic one-step espresso maker, 1 group, 6,5 liter steam/coffee boiler, 1x1,7 kg and 1x1,2 kg coffee hopper, programmable water and steam, Cappuccinatore device for hot milk and foam drinks, Steamair

### General Features

Super automatic one-step espresso maker with automated in-the-cup milk drink delivery. This unit is typically operated for capacities upward of 30lbs. per week. Designed for rugged commercial application and high performance during rush periods. 60,000 cycle piston seals require the Tango the least amount of intervention. Its stainless steel brewing chamber and software design replicate and consistently deliver infusion parameters found in barista controlled equipment. Adjustable and transferable settings via touch screen and USB. Automated steam and foaming wand for milk drinks.

# TANGO ST SOLO 121, Steamair

## Main Features

- Auto cleaning program.
- 1 group full-automatic machine.
- 6.5 liter steam/coffee boiler.
- The super automatic coffee machine Tango® ST Solo takes up a 7" color touch screen user interface to control intuitively the TANGO® group head recognized for its exceptional coffee extraction quality. It aims to automatically transform coffee and fresh milk into a variety of espresso beverages.
- The machine is able to create and compose a choice of 48 drinks menu and delivers 2 drinks simultaneously operating water and steam: it impresses its users with an exceptional result in every cup, and the quality of its equipment makes it a highly reliable choice for demanding professional use.
- 1 x Tango Cappuccinatore device with double feature L: for hot milk and C: for foam by air injection.
- Programmable water and steam.
- Delivery Capacity: Espresso 40ml: 270 cups/h Lungo 100ml: 180 cups/h Hot Water: 36 L/h Cappuccino 100ml: 240 cups/h Latte 100ml: 180 cups/h
- To obtain milk based beverages, the side milk refrigerator is needed.
- Steamair milk auto-frother programmable outlet.

## Construction

- PID (proportional-integral-derivative) Temperature control: a precise controller algorithm system that gives consistency and accuracy to brewing temperature management system.
- 2 coffee grinders (1 x 1,7 kg & 1 x 1,2 kg coffee hoppers).
- LCD Touchscreen.
- LED lights on body.

## Optional Accessories

- RAISED FEET KIT PNC 871041

# TANGO ST SOLO 121, Steamair

## Electric

Supply voltage:

602745  
(SOLOST121SAUL) 220 V/1 ph/60 Hz

Electrical power, max: 5.7 kW

Plug type:

## Water:

Cold water temperature  
(min/max): 5 / 60 °C

## Key Information:

External dimensions,  
Width: 17 13/16" (453 mm)

External dimensions,  
Depth: 24 3/4" (629 mm)

External dimensions,  
Height: 29 5/8" (752 mm)

External dimensions,  
Weight: 216 lbs (98 kg)

Net weight: 216 lbs (98 kg)

Shipping width: (1100 mm)

Shipping depth: (750 mm)

Shipping height: (840 mm)

Shipping weight: lbs (117 kg)

Shipping volume: 0.7 m<sup>3</sup>

## Certifications



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2024.04.09

Part of  Electrolux  
Professional  
Group

# UNIC