

TANGO ST DUO 220, Steamair



Ref602748 (DUOST220SAUL)

Super automatic two-step espresso maker, 2 groups, 2x6,5 liter steam/coffee boiler, 2x1,7 kg coffee hopper, programmable water, Steamair.

General Features

Dual Group super automatic two-step espresso maker with automated steam and foaming wand for milk drinks. This unit is typically operated for capacities upward of 48 lbs. per week. Designed for rugged commercial application and high performance during rush periods. Two 60,000 cycle piston seals require the Duo the least amount of intervention. The two independent stainless steel brewing chambers and software design replicate and consistently deliver infusion parameters found in barista controlled equipment. Adjustable and transferable settings via touch screen and USB.

TANGO ST DUO 220, Steamair

Main Features

- Steamair milk auto-frother programmable outlet.
- 2 groups full-automatic machine.
- 2 x 6.5 liter steam/coffee boiler.
- Programmable hot water.
- The machine is able to create and compose a choice of 96 drinks menu and delivers 4 drinks simultaneously: the Tango® ST Duo is the unique machine of the automatic machines market offering such level of performance with the warranty of an exceptional extraction quality.
- The super automatic coffee machine Tango® ST Duo has two separate 7" screens to control the patented TANGO® double group head with its international recognized reliability.
- With a minimum 60cm width for a 2 groups super automatic coffee machine, the Tango® ST Duo is the ideal unit for businesses aiming to automatically transform coffee and fresh milk into a variety of espresso coffee beverages.
- 2 coffee grinders (2 x 1,7 kg coffee hoppers).

Construction

- PID (proportional-integral-derivative) Temperature control: a precise controller algorithm system that gives consistency and accuracy to brewing temperature management system.
- LCD Touchscreen.
- LED lights on body.

Optional Accessories

- - NOT TRANSLATED - PNC 871041

TANGO ST DUO 220, Steamair

Electric

Supply voltage:

602748
(DUOST220SAUL) 220 V/1 ph/60 Hz

Electrical power, max: 5.7 kW

Plug type:

Water:

Cold water temperature
(min/max): 5 / 60 °C

Key Information:

External dimensions,
Width: 23 3/4" (603 mm)

External dimensions,
Depth: 24 3/4" (629 mm)

External dimensions,
Height: 29 5/8" (752 mm)

External dimensions,
Weight: 262 lbs (119 kg)

Net weight: 262 lbs (119 kg)

Shipping width: (1100 mm)

Shipping depth: (750 mm)

Shipping height: (840 mm)

Shipping weight: lbs (148 kg)

Shipping volume: 0.7 m³

Certifications



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2023.05.26

Part of  Electrolux
Professional
Group

UNIC