

Classic e 2 groups



**Ref: 604035
(CH2.CB.230.3K)**

Traditional Espresso Machine

- 2 Groups
- Cool Touch Steam - Hot Water - Cool Touch Steam
- Inox
- 230 V 1N 50~Hz 3kW
- CE/CB Certified

General Features

The Classic e's elegant lines are underlined by a control board featuring new control buttons. User-friendly and low-maintenance, it delivers features that ensure perfect coffee extraction of consistent quality, and high performance during periods of intensive use.

Classic e 2 groups

Main Features

- Heavy duty components and welded construction, a direct mounted boiler group head for thermal stability and reliable extraction, easy access to components for uncomplicated servicability, and unlimited steam.
- Maestro brew group: directly to boiler group heads are mounted for shot temperature stability.
- 4 programmable volume keys per group + Semi-automatic key for each group for manual control.
- Programmable water and steam.
- Automatic cleaning cycle.
- Manual Steamglide lever.
- Cool touch steam outlets to control steam without the risk of burns, easier to clean after each use

Construction

- Built-in cup warmer.
- Stainless steel body.
- PID (proportional-integral-derivative) Temperature control: a precise controller algorithm system that gives consistency and accuracy to brewing temperature management system.

Sustainability

- Standby mode for controlled management of energy consumption

Included Accessories

- 1 of Filter holder for one cup PNC 871002
- 2 of Filter holder for two cups PNC 871003

Optional Accessories

- Filter holder for one cup PNC 871002
- Filter holder for two cups PNC 871003
- Filter holder for three cups PNC 871004
- Knock box drawer for 2-group machines PNC 871006
- Filter for one cup, 12 gr PNC 871017
- Filter for two cups, 18 gr PNC 871018
- Stainless steel knock box drawer PNC 871019

UNIC

Classic e 2 groups

Electric

Supply voltage: 200-240 V/1N ph/50/60 Hz

Electrical power, max: 3.6 kW

Current consumption: 15 Amps

Plug type: Cable without plug

Water:

Cold water temperature (min/max): 5 / 60 °C

Key Information:

Net weight: 54 kg

Shipping weight: 80 kg

Shipping height: 840 mm

Shipping width: 1100 mm

Shipping depth: 750 mm

Shipping volume: 0.69 m³

Certifications



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2026.02.11

Part of



Electrolux
Professional
Group

UNIC

