Classic e 3 groups



Ref: 604065 (CH3.CE.400.4.7K)

Traditional Espresso Machine

- · 3 Groups
- · Cool Touch Steam Hot Water Cool Touch Steam
- Inox
- · 400 V 3N 50~Hz 4,7kW
- · CE/CB Certified

General Features

The Classic e's elegant lines are underlined by a control board featuring new control buttons. User-friendly and low-maintenance, it delivers features that ensure perfect coffee extraction of consistent quality, and high performance during periods of intensive use.



Classic e 3 groups

Main Features

- Heavy duty components and welded construction, a direct mounted boiler group head for thermal stability and reliable extraction, easy access to components for uncomplicated servicability, and unlimited steam.
- Maestro brew group: directly to boiler group heads are mounted for shot temperature stability.
- 4 programmable volume keys per group + Semi-automatic key for each group for manual control.
- Programmable water and steam.
- Automatic cleaning cycle.
- Manual Steamglide lever.
- Cool touch steam outlets to control steam without the risk of burns, easier to clean after each use

Construction

- Built-in cup warmer.
- Stainless steel body.
- PID (proportional-integral-derivative)
 Temperature control: a precise controller algorithm system that gives consistency and accuracy to brewing temperature management system.

Sustainability

• Standby mode for controlled management of energy consumption

Included Accessories		
• 1 of Filter holder for one cup	PNC 871002	
• 3 of Filter holder for two cups	PNC 871003	
Optional Accessories		
 Filter holder for one cup 	PNC 871002	
 Filter holder for two cups 	PNC 871003	
• Filter holder for three cups	PNC 871004	
 Knock box drawer for 3-group machines 	PNC 871007	
• Filter for one cup, 12 gr	PNC 871017	
• Filter for two cups, 18 gr	PNC 871018	
• Stainless steel knock box drawer	PNC 871019	



Classic e 3 groups

Electric

Supply voltage: 400 V/3N ph/50/60 Hz

Electrical power, max: 4.7 kW **Current consumption:** 7.2 Amps

Plug type: Cable without plug

Water:

Cold water temperature

5/60°C (min/max):

Key Information:

Net weight: 76 kg **Shipping weight:** 97 kg **Shipping height:** 840 mm **Shipping width:** 1320 mm Shipping depth: 750 mm **Shipping volume:** $0.83 \, \text{m}^3$

Certifications











The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2025.12.19





