

## Classic e 3 groups



---

**Ref: 604065  
(CH3.CE.400.4.7K)**

Traditional Espresso Machine

- 3 Groups
- Cool Touch Steam - Hot Water - Cool Touch Steam
- Inox
- 400 V 3N 50~Hz 4,7kW
- CE/CB Certified

### General Features

The Classic e's elegant lines are underlined by a control board featuring new control buttons. User-friendly and low-maintenance, it delivers features that ensure perfect coffee extraction of consistent quality, and high performance during periods of intensive use.

**CH3.CE.400.4.7K**

**UNIC**

# Classic e 3 groups

## Main Features

- Heavy duty components and welded construction, a direct mounted boiler group head for thermal stability and reliable extraction, easy access to components for uncomplicated servicability, and unlimited steam.
- Maestro brew group: directly to boiler group heads are mounted for shot temperature stability.
- 4 programmable volume keys per group + Semi-automatic key for each group for manual control.
- Programmable water and steam.
- Automatic cleaning cycle.
- Manual Steamglide lever.
- Cool touch steam outlets to control steam without the risk of burns, easier to clean after each use

## Construction

- Built-in cup warmer.
- Stainless steel body.
- PID (proportional-integral-derivative) Temperature control: a precise controller algorithm system that gives consistency and accuracy to brewing temperature management system.

## Sustainability

- Standby mode for controlled management of energy consumption

## Included Accessories

- 1 of Filter holder for one cup PNC 871002
- 3 of Filter holder for two cups PNC 871003

## Optional Accessories

- Filter holder for one cup PNC 871002
- Filter holder for two cups PNC 871003
- Filter holder for three cups PNC 871004
- Knock box drawer for 3-group machines PNC 871007
- Filter for one cup, 12 gr PNC 871017
- Filter for two cups, 18 gr PNC 871018
- Stainless steel knock box drawer PNC 871019

**UNIC**

# Classic e 3 groups

## Electric

**Supply voltage:** 400 V/3N ph/50/60 Hz

**Electrical power, max:** 4.7 kW

**Current consumption:** 7.2 Amps

**Plug type:** Cable without plug

## Water:

**Cold water temperature (min/max):** 5 / 60 °C

## Key Information:

**Net weight:** 76 kg

**Shipping weight:** 97 kg

**Shipping height:** 840 mm

**Shipping width:** 1320 mm

**Shipping depth:** 750 mm

**Shipping volume:** 0.83 m<sup>3</sup>

## Certifications



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2026.02.11

Part of



Electrolux  
Professional  
Group

**UNIC**

