TANGO ACE 120, Steamair



Ref: 602617 (UTANGOACE1SA)

Super Automatic Espresso Machine

- · 1 Group
- · 2 Grinders
- · No Milk System Steamair Std Hot Water
- · 380-415V 3N 50/60~Hz
- · CE/CB Certified
- · Shiny Black

General Features

The Tango® Ace impresses its users with an exceptional result in every cup, and the quality of its equipment makes it a highly reliable choice for demanding professional use.

The Tango® Ace fitted with a 7 inches touchscreen, offers a 48 drinks menu, all customizable. Milk-based drinks can be easily prepared with the Cappuccinator device or the Steamair milk auto-frother to process fresh milk into specialty coffee drinks as cappuccino, latte, mocha...



TANGO ACE 120, Steamair

Main Features

- 1 group full-automatic machine.
- 6.5 liter steam/coffee boiler.
- Auto cleaning program.
- Steamair milk auto-frother programmable outlet.
- The super automatic coffee machine Tango® Ace impresses its users with an exceptional result in every cup, and the quality of its equipment makes it a highly reliable choice for demanding professional use.
- The Tango® Ace comes in 3 different colors: shiny white, glossy black and brushed stainless steel, fitted with a new 7" color touch screen user interface. This full automatic coffee machine has a 48 drinks menu, all customizable and comprehensive with the addition of the Cappuccinatore device to process fresh into specialty coffee drinks as cappuccino, latte, mocha...
- Delivery capacity:

Espresso 40ml: 220 cups/h Lungo 100ml: 150 cups/h

Hot water: 30 L/h

Construction

- 2 coffee grinders (1 x 1,7 kg & 1 x 1,2 kg coffee hoppers).
- LCD Touchscreen.
- PID (proportional-integral-derivative)
 Temperature control: a precise controller algorithm system that gives consistency and accuracy to brewing temperature management system.

Optional Accessories

TANGO hotel/breakfast service kit PNC 871022

Coffee ground direct discharge chute PNC 871023



TANGO ACE 120, Steamair

Electric

Supply voltage: 400 V/3N ph/50 Hz

Electrical power max.: 5.2 kW

Plug type: Cable without plug

Water:

Cold water temperature

5/60°C (min/max):

Key Information:

Net weight: 103 kg Shipping volume: 0.69 m³

Sustainability

Current consumption: 7.5 Amps

Certifications







The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2025.04.02





