

# TANGO ACE 121, Cappuccinatore device, Self version



**Ref: 602620**  
**(UTANGOACE1SELFCL)**

Full-automatic machine, 1 group, 220x40 ml espresso cup/hr, 6,5 liter steam/coffee boiler, 1x1,7 kg and 1x1,2 kg coffee hopper, programmable water, Cappuccinatore device for hot milk and foam drinks

## General Features

The Tango® ACE fully takes advantage of the reliability, usability and exceptional extraction quality that has established the reputation of the TANGO® range.

In its Self version, the Tango® ACE comes with lockers for bean hoppers and waste coffee drawer, it has no steam outlet neither ground coffee box for security reason. The Tango® ACE Self version is ideal for using in all self-service areas with its self-explanatory 7" color touch screen user interface easy to use.

With the addition of the Cappuccinatore device, the Tango® ACE Self offers the choice of fresh milk-based beverages at the push of a button.

# TANGO ACE 121, Cappuccinatore device, Self version

## Main Features

- 1 group full-automatic machine with self service configuration.
- 6.5 liter steam/coffee boiler.
- Auto cleaning program.
- In its Self version, the Tango® ACE comes with lockers for bean hoppers and waste coffee drawer, it has no steam outlet neither ground coffee box for security reason. The Tango® ACE Self version is ideal for using in all self-service areas with its self-explanatory 7" color touch screen user interface easy to use.
- Programmable hot water.
- Tango Cappuccinatore device with double feature L: for hot milk and C: for foam by air injection.
- The Tango® ACE fully takes advantage of the reliability, usability and exceptional extraction quality that has established the reputation of the TANGO® range.
- With the Cappuccinatore device, the Tango® ACE Self offers the choice of fresh milk-based beverages at the push of a button.

## Construction

- 2 coffee grinders (1 x 1,7 kg & 1 x 1,2 kg coffee hoppers).
- LCD Touchscreen.
- PID (proportional-integral-derivative) Temperature control: a precise controller algorithm system that gives consistency and accuracy to brewing temperature management system.
- Safety locks.

## Optional Accessories

- Side milk refrigerator 8 liter nominal capacity for up to 4 liter milk containers PNC 871014
- Side milk refrigerator 8 liter nominal capacity for up to 4 liter milk containers with digital display PNC 871015
- TANGO hotel/breakfast service kit PNC 871022
- Coffee ground direct discharge chute PNC 871023

# TANGO ACE 121, Cappuccinatore device, Self version

## Electric

Supply voltage:

602620  
(UTANGOACE1SELFCLC)400 V/3N ph/50 Hz

Electrical power max.: 5.2 kW

Current consumption: 14.5 Amps

Plug type: Cable without plug

## Water:

Cold water temperature

(min/max): 5 / 60 °C

## Key Information:

External dimensions,

Width: 448 mm

External dimensions,

Depth: 627 mm

External dimensions,

Height: 766 mm

Net weight: 91 kg

Shipping volume: 0.69 m<sup>3</sup>

## Certifications




The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2023.03.14

Part of



Electrolux  
Professional  
Group



# UNIC